


1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: BUTLER		SE 1/4 NW 1/4 SE 1/4	3	T 29 S	R 3 EW
Distance and direction from nearest town or city street address of well if located within city? From the SE corner of Sec. 3					
1506' North, 1484' East					
2 WATER WELL OWNER: Craig Van Fleet					
RR#, St. Address, Box #: 13275 SW 186th Terrace					
City, State, ZIP Code: Rose Hill, Ks. 67133					
Board of Agriculture, Division of Water Resources					
Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 91 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 65 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 50 ft. below land surface measured on mo/day/yr 9/14/94			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield 15+ gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 1.0 in. to .91 ft. and in. to ft.			
		WELL WATER TO BE USED AS:			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes No			
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS Glued Clamped					
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded					
7 Fiberglass Threaded					
Blank casing diameter 5 in. to 50 ft. Dia in. to ft. Dia in. to ft.					
Casing height above land surface 18 in. weight 160 lbs./ft. Wall thickness or gauge No.					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement					
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)					
12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)					
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes					
7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 90 ft. to 50 ft. From ft. to ft.					
From ft. to ft. From ft. to ft.					
GRAVEL PACK INTERVALS: From 91 ft. to 45 ft. From ft. to ft.					
From ft. to ft. From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 23 ft. to 10 (3) ft. From 10 ft. to 3 (2) ft. From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)					
13 Insecticide storage					
Direction from well? NNE					
How many feet? 225					
LITHOLOGIC LOG					
FROM	TO			FROM	TO
0.0	1.0	Top Soil			
1.0	30.0	Yellow gray blocky shale with thin Limestone stringers becoming less fissal downward			
30.0	37.0	Brownish shale			
37.0	40.0	Gray, yellow gray shale			
40.0	48.0	Reddish purple clay with greenish blue clay inclusions			
48.0	54.0	Gray, yellow gray shale			
54.0	58.0	Lighter gray shale			
58.0	65.0	Gray clay			
65.0	80.0	Yellow gray fissal shale			
80.0	89.0	Yellow gray limestone			
89.0	91.0	Yellow gray shale			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9/14/94 and this record is true to the best of my knowledge and belief. Kansas					
Water Well Contractor's License No. 279 This Water Well Record was completed on (mo/day/yr) 10/4/94					
under the business name of Fudge Drilling by (signature) Melvin R. Fudge					