

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <u>Butler</u>	<u>SW 1/4 NW 1/4 NE 1/4</u>	<u>23</u>	T <u>29</u> S	R <u>4</u> EW

Distance and direction from nearest town or city street address of well if located within city?

3 miles east of Douglass on 210 St. South

2 WATER WELL OWNER:	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #: <u>Kirby Hill</u> <u>6319 W. 210 St</u>	Application Number:
City, State, ZIP Code: <u>Douglass, KS 67039</u>	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: <u>85</u> ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. <u>62</u> ft. 2. <u>1.8</u> ft. 3. <u>62</u> ft. WELL'S STATIC WATER LEVEL <u>1.8</u> ft. below land surface measured on mo/day/yr Pump test data: Well water was <u>50</u> gpm: Well water was <u>1.2</u> ft. after <u>12</u> hours pumping <u>50</u> gpm Bore Hole Diameter <u>1.2</u> in. to <u>1.2</u> ft. and <u>1.2</u> in. to <u>1.2</u> ft. WELL WATER TO BE USED AS: ☒ 1 Domestic ☐ 3 Feedlot ☐ 6 Oil field water supply ☐ 9 Dewatering ☐ 12 Other (Specify below) ☐ 2 Irrigation ☐ 4 Industrial ☐ 7 Lawn and garden only ☐ 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes <u>No</u> If yes, mo/day/yr sample was submitted <u>Water Well Disinfected? Yes No</u>

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: <u>Glued</u> <u>Clamped</u>
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	10 Asbestos-cement
Blank casing diameter <u>5</u> in. to <u>5</u> ft. Dia			11 Other (specify)
Casing height above land surface <u>12</u> in. weight <u>160</u> lbs./ft. Wall thickness or gauge No.			12 None used (open hole)
TYPE OF SCREEN OR PERFORATION MATERIAL:	5 Fiberglass	8 RMP (SR)	
1 Steel	3 Stainless steel	9 ABS	
2 Brass	4 Galvanized steel		
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	6 Wire wrapped	9 Drilled holes	
2 Louvered shutter	7 Torch cut	10 Other (specify)	
SCREEN-PERFORATED INTERVALS:	From <u>65</u> ft. to <u>85</u> ft.		
GRAVEL PACK INTERVALS:	From <u>20</u> ft. to <u>85</u> ft.		

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout intervals: From <u>3</u> ft. to <u>20</u> ft.				
What is the nearest source of possible contamination:	10 Livestock pens	14 Abandoned water well		
1 Septic tank	11 Fuel storage	15 Oil well/Gas well		
2 Sewer lines	12 Fertilizer storage	16 Other (specify below)		
3 Watertight sewer lines	13 Insecticide storage			
4 Lateral lines				
5 Cess pool				
6 Seepage pit				
7 Pit privy				
8 Sewage lagoon				
9 Feedyard				
Direction from well?	How many feet? <u>50+</u>			

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	4	dirt			
4	12	clay			
12	30	gray shale			
30	35	green shale			
35	50	red rock			
50	70	lime			
70	85	shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>7/30/04</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>943</u> This Water Well Record was completed on (mo/day/yr) <u>8/20/04</u> under the business name of <u>Rossini Well Drilling</u> by (signature) <u>Johnny Rossini</u>
