

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>Butler</u>		<u>SE 1/4 SW 1/4 SW 1/4</u>	<u>32</u>	<u>T 29 S</u>	<u>R 4 E</u>
Distance and direction from nearest town or city street address of well if located within city? <u>2 miles south of Douglass, 1/2 mile west</u>					
2 WATER WELL OWNER: <u>JL Frakes</u>		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box #: <u>103 S. Forest</u>		Application Number:			
City, State, ZIP Code: <u>Douglass, KS 67039</u>					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <u>80</u> ft. ELEVATION: <u>60</u> ft.			
		Depth(s) Groundwater Encountered 1. <u>60</u> ft. 2. <u>60</u> ft. 3. <u>60</u> ft.			
		WELL'S STATIC WATER LEVEL <u>60</u> ft. below land surface measured on mo/day/yr			
		Pump test data: Well water was <u>30</u> gpm. Well water was <u>30</u> gpm. hours pumping <u>30</u> gpm.			
		Bore Hole Diameter: <u>12</u> in. to <u>12</u> in. and <u>12</u> in. to <u>12</u> in.			
WELL WATER TO BE USED AS:		5 Public water supply 8 Air conditioning 11 Injection well 6 Oil field water supply 9 Dewatering 12 Other (Specify below) ☒ Domestic 3 Feedlot 7 Lawn and garden only 10 Monitoring well 2 Irrigation 4 Industrial			
Was a chemical/bacteriological sample submitted to Department? Yes.....No..... If yes, mo/day/yr sample was submitted		Water Well Disinfected? Yes <u>Glued</u> No			
5 TYPE OF BLANK CASING USED:		5 Wrought iron 8 Concrete tile CASING JOINTS: <u>Glued</u> Clamped 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded <u>PVC</u> 4 ABS 7 Fiberglass Threaded			
Blank casing diameter <u>5</u> in. to <u>5</u> ft., Dia. <u>12</u> in. to <u>12</u> ft., Dia. <u>160</u> lbs./ft. Wall thickness or gauge No. <u>12</u>					
Casing height above land surface <u>12</u> in., weight <u>160</u> lbs./ft.					
TYPE OF SCREEN OR PERFORATION MATERIAL:		1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:		1 Continuous slot <u>3 Mill slot</u> 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)			
SCREEN-PERFORATED INTERVALS: From <u>60</u> ft. to <u>80</u> ft., From <u>60</u> ft. to <u>80</u> ft., From <u>60</u> ft. to <u>80</u> ft., From <u>60</u> ft. to <u>80</u> ft.					
GRAVEL PACK INTERVALS: From <u>20</u> ft. to <u>80</u> ft., From <u>20</u> ft. to <u>80</u> ft., From <u>20</u> ft. to <u>80</u> ft., From <u>20</u> ft. to <u>80</u> ft.					
6 GROUT MATERIAL:		1 Neat cement 2 Cement grout <u>3 Bentonite</u> 4 Other Grout Intervals: From <u>3</u> ft. to <u>20</u> ft., From <u>3</u> ft. to <u>20</u> ft., From <u>3</u> ft. to <u>20</u> ft., From <u>3</u> ft. to <u>20</u> ft.			
What is the nearest source of possible contamination:		1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage			
Direction from well?		How many feet? <u>50</u>			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	earth			
3	15	clay			
15	30	gray shale			
30	33	green shale			
33	45	red rock			
45	65	lime			
65	80	shale			
RECEIVED SEP 01 2004 BUREAU OF WATER					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>7/24/04</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>943</u> This Water Well Record was completed on (mo/day/yr) <u>5/29/04</u> under the business name of <u>Rebecca Well Drilling</u> by (signature) <u>Rebecca Well Drilling</u>					