

1 LOCATION OF WATER WELL:		Fraction <u>NW</u> <u>NE</u> <u>NW</u>		Section Number	Township Number	Range Number
County: <u>Butler</u>		<u>SE</u> <u>SE</u> <u>SE</u>		<u>13</u>	T <u>29</u> S	R <u>4</u> <u>EW</u>
Distance and direction from nearest town or city street address of well if located within city? <u>3 1/2 E, 1 N of Douglass S.E. side</u>						
2 WATER WELL OWNER: <u>Dale Henning</u>						
RR#, St. Address, Box #: <u>120 S. Gordon</u>				Board of Agriculture, Division of Water Resources		
City, State, ZIP Code: <u>Wichita, KS 67213</u>				Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <u>95'</u> ft. ELEVATION:				
		Depth(s) Groundwater Encountered 1. <u>32</u> ft. 2. ft. 3. ft.				
		WELL'S STATIC WATER LEVEL <u>25</u> ft. below land surface measured on mo/day/yr <u>6/15/90</u>				
		Pump test data: Well water was ft. after hours pumping gpm				
		Est. Yield <u>25</u> gpm: Well water was ft. after hours pumping gpm				
		Bore Hole Diameter: <u>10</u> in. to ft., and in. to ft.				
		WELL WATER TO BE USED AS:				
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well				
		Was a chemical/bacteriological sample submitted to Department? Yes No ☒ If yes, mo/day/yr sample was submitted				
		Water Well Disinfected? Yes ☒ No				
5 TYPE OF BLANK CASING USED:						
1 Steel		3 RMP (SR)		5 Wrought iron		8 Concrete tile
2 PVC		4 ABS		6 Asbestos-Cement		9 Other (specify below)
				7 Fiberglass		CASING JOINTS: Glued ☒ Clamped
						Welded
						Threaded
Blank casing diameter <u>5</u> in. to ft., Dia in. to ft., Dia in. to ft.						
Casing height above land surface <u>12</u> in., weight lbs./ft. Wall thickness or gauge No. <u>160</u>						
TYPE OF SCREEN OR PERFORATION MATERIAL:						
1 Steel		3 Stainless steel		5 Fiberglass		7 PVC
2 Brass		4 Galvanized steel		6 Concrete tile		8 RMP (SR)
						9 ABS
						10 Asbestos-cement
						11 Other (specify)
						12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:						
1 Continuous slot		3 Mill slot		5 Gauzed wrapped		8 Saw cut
2 Louvered shutter		4 Key punched		6 Wire wrapped		9 Drilled holes
				7 Torch cut		10 Other (specify)
						11 None (open hole)
SCREEN-PERFORATED INTERVALS: From <u>75</u> ft. to <u>95</u> ft., From ft. to ft.						
GRAVEL PACK INTERVALS: From <u>20</u> ft. to <u>95</u> ft., From ft. to ft.						
GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other						
Grout intervals: From <u>0</u> ft. to <u>20</u> ft., From ft. to ft., From ft. to ft.						
What is the nearest source of possible contamination:						
1 Septic tank		4 Lateral lines		7 Pit privy		10 Livestock pens
2 Sewer lines		5 Cess pool		8 Sewage lagoon		11 Fuel storage
3 Watertight sewer lines		6 Seepage pit		9 Feedyard		12 Fertilizer storage
						13 Insecticide storage
						14 Abandoned water well
						15 Oil well/Gas well
						16 Other (specify below)
Direction from well? <u>Down Slope</u>						How many feet? <u>50+</u>
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS	
0	4	dirt				
4	6	green shale				
6	75	yellow clay				
75	87	red clay				
87	95	shaly lime				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>6/15/90</u> and this record is true to the best of my knowledge and belief. Kansas						
Water Well Contractor's License No. <u>493</u> This Water Well Record was completed on (mo/day/yr) <u>6/19/90</u>						
under the business name of <u>Reiserer Well Drilling</u> by (signature) <u>Jerry Reiserer</u>						
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send two copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-7320. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.						