

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>Butler</u>		<u>SE 1/4 SW 1/4 NE 1/4</u>	<u>32</u>	<u>T 29 S</u>	<u>R 4 EW</u>
Distance and direction from nearest town or city street address of well if located within city? <u>3 Mile S of Douglas Kan</u>					
2 WATER WELL OWNER:		61039			
RR#, St. Address, Box # :		Board of Agriculture, Division of Water Resources			
City, State, ZIP Code :		Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <u>165</u> ft. ELEVATION: <u>125</u> ft.			
		Depth(s) Groundwater Encountered <u>1. 125</u> ft. 2. <u>50</u> ft. 3. <u>165</u> ft.			
		WELL'S STATIC WATER LEVEL <u>50</u> ft. below land surface measured on mo/day/yr			
		Pump test data: Well water was <u>35</u> gpm. Well water was <u>17</u> ft. after <u>160</u> hours pumping <u>1214</u> gpm			
		Est. Yield <u>35</u> gpm. Well water was <u>17</u> ft. after <u>160</u> hours pumping <u>1214</u> gpm			
Bore Hole Diameter <u>9 1/2</u> in. to <u>160</u> ft. and <u>1214</u> in. to <u>165</u> ft.		WELL WATER TO BE USED AS:			
1 Domestic		3 Feedlot	6 Oil field water supply	9 Dewatering	12 Other (Specify below)
2 Irrigation		4 Industrial	7 Lawn and garden only	10 Monitoring well	
Was a chemical/bacteriological sample submitted to Department? Yes <u>X</u> No <u>X</u> ; If yes, mo/day/yr sample was submitted <u>1214</u>					
Water Well Disinfected? Yes <u>X</u> No <u>X</u>					
5 TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <u>X</u> Clamped <u>X</u>
2 PVC		4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded <u>X</u>
Blank casing diameter <u>5</u> in. to <u>17</u> ft. Dia <u>18</u> in. to <u>160</u> ft. Dia <u>1214</u> in. to <u>165</u> ft.		7 Fiberglass	Threaded <u>X</u>		
Casing height above land surface <u>18</u> in. weight <u>160</u> lbs./ft. Wall thickness or gauge No. <u>1214</u>					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel		3 Stainless steel	5 Fiberglass	8 RMP (SR)	10 Asbestos-cement
2 Brass		4 Galvanized steel	6 Concrete tile	9 ABS	11 Other (specify)
12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot		3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter		4 Key punched	6 Wire wrapped	9 Drilled holes	
7 Torch cut					
10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From <u>70</u> ft. to <u>165</u> ft. From <u>165</u> ft. to <u>165</u> ft.					
GRAVEL PACK INTERVALS: From <u>70</u> ft. to <u>165</u> ft. From <u>165</u> ft. to <u>165</u> ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout <u>X</u> Bentonite 4 Other					
Grout Intervals: From <u>0</u> ft. to <u>23</u> ft. From <u>23</u> ft. to <u>165</u> ft. From <u>165</u> ft. to <u>165</u> ft.					
What is the nearest source of possible contamination:					
1 Septic tank		4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines		5 Cess pool	<u>X</u> Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines		6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
Direction from well? <u>S W</u>		How many feet? <u>250</u>			
FROM TO		LITHOLOGIC LOG		FROM TO PLUGGING INTERVALS	
0 3		Soil			
3 15		Rock			
15 25		Clay			
25 165		Shale & Lime			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <u>X</u> constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>3/22/94</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>251</u> This Water Well Record was completed on (mo/day/yr) <u>4/13/94</u> under the business name of <u>Winter Well Drill</u> by (signature) <u>Charles Winter</u>					