

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Butler		NW 1/4 SW 1/4 NE 1/4	13	T 29 S	R 4 E
Distance and direction from nearest town or city street address of well if located within city? From the SE corner of Sec., 13 3740' N., 2080' W.					
2 WATER WELL OWNER:		Wilford Darter			
RR#, St. Address, Box # :		Rt 2 Box 358			
City, State, ZIP Code :		Douglass, Ks. 67039			
		Board of Agriculture, Division of Water Resources Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 36 ft. ELEVATION:			
1 Mile		Depth(s) Groundwater Encountered 1. 30 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 12.5 ft. below land surface measured on mo/day/yr 9/26/94			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield 10+ gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 1.0 in. to 36 ft. and in. to ft.			
WELL WATER TO BE USED AS:		5 Public water supply 8 Air conditioning 11 Injection well			
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)					
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well					
Was a chemical/bacteriological sample submitted to Department? Yes No ☒ If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes ☒ No					
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile		CASING JOINTS: Glued ☒ Clamped			
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below)		Welded			
		Threaded			
Blank casing diameter 5 in. to 13 ft. Dia in. to ft. Dia in. to ft.					
Casing height above land surface 18 in., weight 160 lbs./ft. Wall thickness or gauge No.					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement					
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)					
		12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)					
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes					
		10 Other (specify)			
SCREEN-PERFORATED INTERVALS: From 13 ft. to 36 ft. From ft. to ft.					
From ft. to ft. From ft. to ft.					
GRAVEL PACK INTERVALS: From 12.5 ft. to 36 ft. From ft. to ft.					
From ft. to ft. From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 12.5 ft. to 10 (2) ft. From 10 ft. to 0 (3) ft. From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)					
		13 Insecticide storage			
Direction from well? WEST How many feet? 107					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0.0	9.0	Top Soil and weathered shale			
9.0	11.0	Yellow gray limestone			
11.0	13.0	Brownish red shale			
13.0	20.0	Gray clay			
20.0	22.0	Limestone			
22.0	24.0	Yellow gray clay			
24.0	27.0	Gray fissal shale			
27.0	35.0	Lighter gray fissal shale			
35.0	36.0	Gray clay			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9/26/94 and this record is true to the best of my knowledge and belief. Kansas					
Water Well Contractor's License No. 279 This Water Well Record was completed on (mo/day/yr) 10/10/94					
under the business name of Fudge Drilling by (signature) <i>Michael R. Fudge</i>					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					