				Mw3				
WATER WELL REC	Form W	Division of Water Resources App. No.						
1 LOCATION OF WATER WELL:		Fraction		Section			Range Number	
County: Neman	1/4 XW 1/4 XW 1/4 NG 1/4			34	T Q S	R / DE W		
Street/Rural Address of Well Location; if unknown, distance & direction from nearest town or intersection: If at owner's address, check here					Global Positioning System (GPS) information:			
New Bldg: 11 North 3rd Street					Latitude: 318346.1.1 (in decimal degrees) Longitude: 40548640 (in decimal degrees)			
					Elevation: (in decimal degrees)			
Senear, Ks.					<u>Datum</u> : ☐ WGS 84, ☐ NAD 83, ☐ NAD 27			
RR#, Street Address, Box #:					Collection Method: GPS unit (Make/Model:)			
City, State, ZIP Code	SW GACKSON LKA, KS 66612		☐ Digital Map/Photo, ☐ Topographic Map, 🔀 Land Survey					
	2K2, KS 66	Est. Accuracy:						
3 LOCATE WELL WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 35					Ω			
SECTION BOX:	Depth(s) Groundwater Encountered (1) 25 ft (2) ft (3)							
N	X: Depth(s) Groundwater Encountered (1).25							
	Pump test data: Well water wasft. after hours pumping gpm							
NW NE	EST. YIELD. gpm. Well water was ft. after hours pumping. gpn Bore Hole Diameter 1.7. in. to 3.5. ft., and in. to ft.							
W E	E Bore Hole Diameter							
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well Domestic Feedlot Oil field water supply Dewatering Other (Specified)							Injection well Other (Specify below)	
SW SE	☐ Irrigation	☐ Industrial ☐	Domestic-lay	zi suppiy vn & gai	y ∐ Do rden DorMo	onitoring well	other (specify below)	
	☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☐ Monitoring well							
S If yes, mo/day/yr sample was submitted								
1 mile Water well disinfected?								
5 TYPE OF CASING USED: Steel X PVC Other								
CASING JOINTS: Glued Clamped Welded Threaded Casing diameter 3.3.15 in. to 30								
Casing diameter and to the intermediate the control of the control								
TYPE OF SCREEN OR PERFORATION MATERIAL: Weightlbs./ft., Wall thickness or gauge No. Alph. T.D								
Steel Stainless Steel PVC Other (Specify)								
Brass Galvanized Steel None used (open hole)								
SCREEN OR PERFORATION OPENINGS ARE:								
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole) Louvered shutter Key punched Wire wrapped Saw cut Gother (specify)								
Louvered shutter Key punched Saw cut Other (specify) SCREEN-PERFORATED INTERVALS: From ft. to ft.								
From								
GRAVEL PACI								
From ft. to ft., From ft. to ft.								
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other College St. ft. to								
What is the nearest source of possible contamination:								
Septic tank Lateral lines Pit privy Livestock pens Insecticide storage Other (specify below)							her (specify below)	
Sewer lines	Sewage lagoon Fuel storage Abandoned water well							
☐ Watertight sewer l Direction from well		it Feedyard	Fertilizer s		∐ Oil well/ga			
FROM TO	LITHOLOG		FROM	TO			UGGING INTERVALS	
0 150 Tags			1110111		1311110.13	00 (0010) 01 1 10		
150 11 WIL	owen sit	to Class oak	tidre	WIL	in Duide	ustreaks)	
11 15 bodo	lish Bin 2	Bray Clark		soft.)			
15 28 Yell	wwgen Me	aven sand	10000	UPG	situella	tulen at 2	21	
28 35 Gell	<u>ow bin sir</u>	My Clay M	2000		(m)	<u> </u>		
		· · · · · · · · · · · · · · · · · · ·	-					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 🗷 constructed, 🗆 reconstructed, or 🗀 plugged								
under my jurisdiction and was completed on (mo/day/year) !!! and this record is true to the best of my knowledge and belief.								
Kansas Water Well Contractor's License No. 132 This Water Well Record was completed on (mo/day/year)								
under the business name INSTRUCTIONS: Use typew	oiCAO.COVI	NONMENTAL	V and DDINT -1	by (s	agnature)(and check the second	of answers Sand these assistance	
(white, blue, pink) to Kansas l	Department of Health	and Environment, Bureau	of Water, Geol	ogy Section	on, 1000 SW Ja	is and theth the corre	Topeka, Kansas 66612-1367.	
Telephone 785-296-5522. Sei	nd one copy to WAT							
http://www.kdheks.gov/waterwell/index.html. KSA 82a-1212								