

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL:		Fraction NW 1/4 NE 1/4 NW 1/4	Section Number 1	Township Number T 2 S	Range Number R 14E E/W																																																																																																
Distance and direction from nearest town or city street address of well if located within city? 1/4 north of Sabetha																																																																																																					
2 WATER WELL OWNER:		City of Sabetha		T.W. #9-89																																																																																																	
RR#, St. Address, Box # :		805 Main		Board of Agriculture, Division of Water Resources																																																																																																	
City, State, ZIP Code :		Sabetha, KS 66534		Application Number: 39,992																																																																																																	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL... 150' ft. ELEVATION: Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL .75' ft. below land surface measured on mo/day/yr 9-14-89 Pump test data: Well water was ft. after hours pumping gpm Est. Yield .15 gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter .8 3/4 in. to ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes <input checked="" type="checkbox"/> No If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <input checked="" type="checkbox"/> No																																																																																																			
5 TYPE OF BLANK CASING USED:		5 Wrought iron 1 Steel 3 RMP (SR) 2 PVC	8 Concrete tile 6 Asbestos-Cement 7 Fiberglass	CASING JOINTS: Glued <input checked="" type="checkbox"/> Clamped Welded Threaded																																																																																																	
Blank casing diameter 5" in. to .0-90 ft., Dia .5" in. to .120-150 ft., Dia in. to ft.																																																																																																					
Casing height above land surface 24" in., weight .2.82 lbs./ft. Wall thickness or gauge No. .258																																																																																																					
TYPE OF SCREEN OR PERFORATION MATERIAL: XX 10' Johnson 7 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)																																																																																																					
SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)																																																																																																					
SCREEN-PERFORATED INTERVALS: From .90 ft. to .100 ft., From ft. to ft. From .100 ft. to .120 ft., From ft. to ft.																																																																																																					
GRAVEL PACK INTERVALS: From .24 ft. to .150 ft., From ft. to ft. From ft. to ft., From ft. to ft.																																																																																																					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From .0 ft. to .24 ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage																																																																																																					
Direction from well? west How many feet? 200'																																																																																																					
<table border="1"> <thead> <tr> <th>FROM</th> <th>TO</th> <th>LITHOLOGIC LOG</th> <th>FROM</th> <th>TO</th> <th>PLUGGING INTERVALS</th> </tr> </thead> <tbody> <tr><td>0</td><td>26</td><td>Clay-Brown</td><td>92</td><td>94</td><td>Shale-Grey</td></tr> <tr><td>26</td><td>28</td><td>Limestone-Yellow</td><td>94</td><td>96</td><td>Limestone-grey-Loose</td></tr> <tr><td>28</td><td>31</td><td>Shale-Yellow</td><td>96</td><td>105</td><td>Limestone-Grey</td></tr> <tr><td>31</td><td>32</td><td>Shale-Red</td><td>105</td><td>122</td><td>Shale-grey</td></tr> <tr><td>32</td><td>34</td><td>Shale-Yellow</td><td>122</td><td>125</td><td>Shale-Red</td></tr> <tr><td>34</td><td>39</td><td>Shale-Red</td><td>125</td><td>130</td><td>Gyp</td></tr> <tr><td>39</td><td>45</td><td>Shale-Yellow</td><td>130</td><td>137</td><td>Shale-Grey</td></tr> <tr><td>45</td><td>49</td><td>Limestone-Yellow</td><td>137</td><td>146</td><td>Shale-Red</td></tr> <tr><td>49</td><td>62</td><td>Shale-Yellow</td><td>146</td><td>150</td><td>Shale-grey</td></tr> <tr><td>62</td><td>71</td><td>Limestone-grey</td><td></td><td></td><td></td></tr> <tr><td>71</td><td>78</td><td>Shale-Grey</td><td></td><td></td><td></td></tr> <tr><td>78</td><td>81</td><td>Shale-Red</td><td></td><td></td><td></td></tr> <tr><td>81</td><td>89</td><td>Shale-Yellow</td><td></td><td></td><td></td></tr> <tr><td>89</td><td>91</td><td>Limestone-Yellow</td><td></td><td></td><td></td></tr> <tr><td>91</td><td>92</td><td>Limestone-Grey</td><td></td><td></td><td></td></tr> </tbody> </table>						FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS	0	26	Clay-Brown	92	94	Shale-Grey	26	28	Limestone-Yellow	94	96	Limestone-grey-Loose	28	31	Shale-Yellow	96	105	Limestone-Grey	31	32	Shale-Red	105	122	Shale-grey	32	34	Shale-Yellow	122	125	Shale-Red	34	39	Shale-Red	125	130	Gyp	39	45	Shale-Yellow	130	137	Shale-Grey	45	49	Limestone-Yellow	137	146	Shale-Red	49	62	Shale-Yellow	146	150	Shale-grey	62	71	Limestone-grey				71	78	Shale-Grey				78	81	Shale-Red				81	89	Shale-Yellow				89	91	Limestone-Yellow				91	92	Limestone-Grey			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS																																																																																																
0	26	Clay-Brown	92	94	Shale-Grey																																																																																																
26	28	Limestone-Yellow	94	96	Limestone-grey-Loose																																																																																																
28	31	Shale-Yellow	96	105	Limestone-Grey																																																																																																
31	32	Shale-Red	105	122	Shale-grey																																																																																																
32	34	Shale-Yellow	122	125	Shale-Red																																																																																																
34	39	Shale-Red	125	130	Gyp																																																																																																
39	45	Shale-Yellow	130	137	Shale-Grey																																																																																																
45	49	Limestone-Yellow	137	146	Shale-Red																																																																																																
49	62	Shale-Yellow	146	150	Shale-grey																																																																																																
62	71	Limestone-grey																																																																																																			
71	78	Shale-Grey																																																																																																			
78	81	Shale-Red																																																																																																			
81	89	Shale-Yellow																																																																																																			
89	91	Limestone-Yellow																																																																																																			
91	92	Limestone-Grey																																																																																																			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9-14-89 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 182 This Water Well Record was completed on (mo/day/yr) 2-4-92 under the business name of STRADER DRILLING CO., INC. by (signature) <i>Dale L. Schrenk</i>																																																																																																					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.																																																																																																					