

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Brown	NE ¼ SE ¼ SW ¼	34	T 2 S	R 15 E E/W

Distance and direction from nearest town or city street address of well if located within city?

County Shop

2 WATER WELL OWNER:	KDHE-BER	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # :	Building 740, Forbes Field	Application Number:
City, State, ZIP Code :	Topeka, Kansas 66620	1219

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 118 ft. ELEVATION: 1219
	Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 63 ft. below land surface measured on mo/day/yr 11/4/94 Pump test data: Well water was ft. after hours pumping gpm Est. Yield NA gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 8 in. to 123 ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes.....No..... X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Welded X
Blank casing diameter 2 in. to 98 ft., Dia in. to ft., Dia in. to ft.			Threaded X
Casing height above land surface 31.2 in., weight lbs./ft. Wall thickness or gauge No. Sch. 40			
TYPE OF SCREEN OR PERFORATION MATERIAL:	2 PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS: From 98 ft. to 118 ft., From ft. to ft.			
GRAVEL PACK INTERVALS: From 97 ft. to 123 ft., From ft. to ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 0 ft. to 20 ft., From 20 ft. to 97 ft., From ft. to ft.				
What is the nearest source of possible contamination:	10 Livestock pens	14 Abandoned water well		
1 Septic tank	4 Lateral lines	7 Pit privy	11 Fuel storage	15 Oil well/Gas well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	16 Other (specify below)
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	13 Insecticide storage	UST
Direction from well? NA			How many feet? 0	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	0.5	Gravel,			GeoCore # 114085
0.5	7	Clay, Medium to Dark Brown			04007074
7	14	Clay, Medium Brown			MW3D
14	20	Shale, Gray Green			Above-ground Cover
20	23	Shale, Light Gray Brown			
23	26	Limestone, Light Gray	71.5	76	Shale, Tan to Gray Green
26	32	Shale, Light to Medium Green to Gray G	76	81	Shale, Very Dark Brown to Black
32	34	Shale, Green to Gray Green	81	95	Interbedded Shale and Limestone, Light Brown, Gr
34	43	Shale, Light Green	95	98	Shale, Medium to Dark Gray
43	48	Shale, Dark Gray to Gray Green	98	107	Limestone, Medium Green Brown
48	60	Shale, Red to Maroon	107	123	Shale, Gray Green to Gray
60	65.5	Shale, Red Brown			
65.5	71.5	Limestone, Light Gray to Gray Brown			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11/4/94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 11/15/94 under the business name of GeoCore Services, Inc. by (signature) <i>Dra R</i>
