


1 LOCATION OF WATER WELL: County: **Brown** Fraction: **NE** 1/4 1/4 1/4 Section Number: **30** Township Number: **T 2 S** Range Number: **R 17 E/W**

Distance and direction from nearest town or city street address of well if located within city?  
**Industrial Park Avenue**

2 WATER WELL OWNER: **Flair Fold Corporation**  
 RR#, St. Address, Box #: **PO Box 355**  
 City, State, ZIP Code: **Hiawatha, KS 66434**  
 Application Number: **1AMW 8**  
 Board of Agriculture, Division of Water Resources

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  4 DEPTH OF COMPLETED WELL: **55.2** ft. ELEVATION: **1122.19**

Depth(s) Groundwater Encountered 1. . . . . ft. 2. . . . . ft. 3. . . . . ft.  
 WELL'S STATIC WATER LEVEL: **6.91** ft. below land surface measured on mo/day/yr **5/26/95**  
 Pump test data: Well water was . . . . . ft. after . . . . . hours pumping . . . . . gpm  
 Est. Yield . . . . . gpm: Well water was . . . . . ft. after . . . . . hours pumping . . . . . gpm  
 Bore Hole Diameter . . . . . in. to . . . . . ft., and . . . . . in. to . . . . . ft.  
 WELL WATER TO BE USED AS:  
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)  
 2 Irrigation 4 Industrial 7 Lawn and garden only **10 Monitoring well**  
 Was a chemical/bacteriological sample submitted to Department? Yes . . . . . No **X**; If yes, mo/day/yr sample was sub-  
 mitted Water Well Disinfected? Yes . . . . . No **X**

5 TYPE OF BLANK CASING USED:  
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued . . . . . Clamped . . . . .  
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded . . . . .  
 Blank casing diameter . . . . . in. to **30.7** ft. Dia. **6** in. to **35.4** ft. Dia . . . . . in. to . . . . . ft.  
 Casing height above land surface . . . . . in., weight **0.10** lbs./ft. Wall thickness or gauge No. **Sch 40**  
 TYPE OF SCREEN OR PERFORATION MATERIAL:  
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement  
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) . . . . .  
 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:  
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)  
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes  
 7 Torch cut 10 Other (specify) . . . . .  
 SCREEN-PERFORATED INTERVALS: From **55.2** ft. to **35.4** ft. From . . . . . ft. to . . . . . ft.  
 GRAVEL PACK INTERVALS: From **55.2** ft. to **32.5** ft. From . . . . . ft. to . . . . . ft.  
 From . . . . . ft. to . . . . . ft. From . . . . . ft. to . . . . . ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other . . . . .  
 Grout Intervals: From **32.5** ft. to **27.6** ft. From **27.6** ft. to **0** ft. From . . . . . ft. to . . . . . ft.  
 What is the nearest source of possible contamination:  
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well  
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well  
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)  
 Direction from well? **Phase II Environmental Assessment**  
 How many feet? **Assessment**

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
		<del>see attached</del>			
<b>0</b>	<b>4.5</b>	silt			
<b>4.5</b>	<b>5.5</b>	sawdust			
<b>5.5</b>	<b>9.5</b>	silt			
<b>9.5</b>	<b>25.5</b>	clay			
<b>25.5</b>	<b>33.5</b>	silt			
<b>33.5</b>	<b>39</b>	sand			
<b>39</b>	<b>40</b>	pyrite			
<b>40</b>	<b>55</b>	sand			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was **(1)** constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) **5/22/95** and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. **102** This Water Well Record was completed on (mo/day/yr) **6-29-95** under the business name of **Layne Inc** by (signature) 