


1 LOCATION OF WATER WELL: County: **Brown** Fraction: **NE 1/4 NE 1/4 SE 1/4** Section Number: **29** Township Number: **T 2 S** Range Number: **R 17 EW**

Distance and direction from nearest town or city street address of well if located within city?
310 N 1st. Hiawatha, KS.

2 WATER WELL OWNER: **Ramona Scheid**
 RR#, St. Address, Box #: **310 N 1st.** Board of Agriculture, Division of Water Resources
 City, State, ZIP Code: **Hiawatha, Ks.** Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  4 DEPTH OF COMPLETED WELL: **45'** ft. ELEVATION:
 Depth(s) Groundwater Encountered: **1 33 1/2'** ft. 2. ft. 3. ft.
 WELL'S STATIC WATER LEVEL: **32' 3"** ft. below land surface measured on **mo/day/yr 7-6-94**
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield gpm: Well water was ft. after hours pumping gpm
 Bore Hole Diameter: **8 1/2'** in. to **45'** ft., and in. to ft.
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only **10 Monitoring well**
 Was a chemical/bacteriological sample submitted to Department? Yes No: **X** If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes **No**

5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded
2 PVC 4 ABS 7 Fiberglass Threaded: **X**
 Blank casing diameter: **2.375** in. to **30'** ft. Dia in. to ft. Dia in. to ft.
 Casing height above land surface: **Flush Mount** in. weight lbs./ft. Wall thickness or gauge No. **SDR 13**
 TYPE OF SCREEN OR PERFORATION MATERIAL: **7 PVC** 10 Asbestos-cement **SCH 40**
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 1 Continuous slot **3 Mill slot** 6 Wire wrapped 9 Drilled holes
 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From **45'** ft. to **30'** ft. From ft. to ft.
 From ft. to ft. From ft. to ft.
 GRAVEL PACK INTERVALS: From **45'** ft. to **27'** ft. From ft. to ft.
 From ft. to ft. From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From **27'** ft. to **7'** ft. From **7'** ft. to **0'** ft. From ft. to ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy **11 Fuel storage** 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage 16 Other (specify below)
 Direction from well? **North** How many feet? **60'**

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3.50	Dk brn silty soil, moist to dry, earthy odor, roots.			
3.50	6	Med brn silty clay till, moist, no odor, iron oxides.			
6	9.50	Gray brn mottled silty clay till, firm, no odor.			
9.50	28.25	Red brn silty clay till, firm, no odor, mottled.			
28.25	45	Yellow brn silty sandy clay till, moist sand, no odor, fine-med grained iron oxides, cobbles, granite sand len at 33 1/2' thick-wet caliche. Olive yellow sandy gravelly clay till, no odor, moist, few cobbles. Wet at 40'			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) **constructed** (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) **7-5-94** and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. **539** This Water Well Record was completed on (mo/day/yr) **7-20-94** under the business name of **JB Environmental Drilling** by (signature) **James Becker**

000591