

WATER WELL RECORD

Form WWC-5

Division of Water Resources App. No.

Blank box for application number

1 LOCATION OF WATER WELL: County: Brown, Fraction NW 1/4 NE 1/4 SW 1/4 NE 1/4, Section Number 4, Township No. T 2 S, Range Number R 17 E W

Street/Rural Address of Well Location; if unknown, distance & direction from nearest town or intersection: From HY73 & 280th St, about 3/4 East & 1/4 South. Global Positioning System (GPS) information: Latitude: .39,90971, Longitude: -95.51482, Elevation: , Datum: WGS 84, NAD 83, NAD 27, Collection Method: GPS unit (Make/Model: Garmin 12xl)

2 WATER WELL OWNER: Jerry & Jane Reschke, RR#, Street Address, Box #: 1515 320th St, City, State, ZIP Code : Hiawatha, KS 66434

3 LOCATE WELL WITH AN "X" IN SECTION BOX: N, E, S, W, 1 mile scale, grid with 'X' in NE quadrant

4 DEPTH OF COMPLETED WELL 78 ft. Depth(s) Groundwater Encountered (1).30 ft. (2) ft. (3) ft. WELL'S STATIC WATER LEVEL 31.1 ft. below land surface measured on mo/day/yr. 05/02/2010. Pump test data: Well water was 52.9 ft. after 1.5 hours pumping 400 gpm EST. YIELD. 450 gpm. Well water was ft. after hours pumping gpm Bore Hole Diameter 30 in. to 78 ft., and in. to ft. WELL WATER TO BE USED AS: Irrigation, Industrial, Domestic-lawn & garden, Monitoring well

5 TYPE OF CASING USED: PVC, CASING JOINTS: Glued, Casing diameter .16 in. to .78 ft., Diameter in. to ft., Diameter in. to ft. Casing height above land surface .20 in., Weight 19.9 lbs./ft., Wall thickness or gauge No. .0615. TYPE OF SCREEN OR PERFORATION MATERIAL: PVC, SCREEN OR PERFORATION OPENINGS ARE: Mill slot, Gauze wrapped, Torch cut, Drilled holes, None (open hole), SCREEN-PERFORATED INTERVALS: From .58 ft. to .78 ft., From ft. to ft., From ft. to ft. 8/16 GRAVEL PACK INTERVALS: From .25 ft. to .78 ft., From ft. to ft., From ft. to ft.

6 GROUT MATERIAL: Bentonite, Grout Intervals: From 5 ft. to 25 ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination: Other (specify below) Ditch, Direction from well NE, Distance from well .70

Table with columns FROM, TO, LITHOLOGIC LOG, FROM, TO, LITHO. LOG (cont.) or PLUGGING INTERVALS. Rows include: 0-4 no sample, 4-17 clay silty brown, 17-24 sand F, 24-30 clay sandy tan, 30-50 sand F-M, 50-72 sand F-C, 72-76 clay gray, 76-77 sand F-M, 77-78 clay gray

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo/day/year) 02/03/2010. Kansas Water Well Contractor's License No. 779. This Water Well Record was completed on (mo/day/year) 05/04/2010 under the business name of Drill-Well, LLC by (signature)

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send three copies (white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell/index.html.