Mathewson East									
WATER WELL RECORD Form WWC-5 Division of Water Resources App. No.									
		OF WATER WELL:	Fraction			on Number	Township No.	Range Number	
	ty: Brov		NE ¼ NE ¼ SW			17	T 2 S	R 17 Z E □W	
Street/Rural Address of Well Location; if unknown, distance & direction					Globa	l Positioning	g System (GPS) i	nformation:	
from nearest town or intersection: If at owner's address, check here .						Latitude: .39.8811940 (in decimal degrees)			
1/4 mile South & 1/4 mile West of intersection of 260th St & HY73						itude: 95.53	197.20	(in decimal degrees)	
·						Elevation: .1081 Datum: ☐ WGS 84, ☑ NAD 83, ☐ NAD 27			
2 WATER WELL OWNER: Dave Mathewson						i: [] WGS 8	4, 🔽 NAD 83, L	J NAD 27	
RR#, Street Address, Box #: PO Box 343					17 (GPS unit (Make/Model: Garmin 12xl			
City, State, ZIP Code : Hiawatha, KS 66434					☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey				
					Est. A	Est. Accuracy:			
	ATE WE	3							
	Ĩ AN "X'								
SECI	SECTION BOX: N Depth(s) Groundwater Encountered (1)								
[[
1 1 1									
w NW									
SW	/ SI	Domestic						Other (Specify below)	
~ï	Ĭ	✓ Irrigation						•••••••	
leanneis In	Was a chemical/bacteriological sample submitted to Department? Yes No								
	S If yes, mo/day/yr sample was submitted								
1 mile Water well disinfected? ✓ Yes □ No									
5 TYPE OF CASING USED: Steel V PVC Other									
CASING JOINTS: Glued Clamped Welded Threaded									
Casing diameter .16 in. to .72 ft., Diameter in. to ft., Diameter in. to ft.									
Casing height above land surface12									
TYPE OF SCREEN OR PERFORATION MATERIAL: ☐ Steel ☐ Stainless Steel									
Brass Galvanized Steel None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:									
☐ Continuous slot									
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)									
SCREEN-PERFORATED INTERVALS: From									
From									
GRAVEL PACK INTERVALS: From									
From									
Grout In		From 5 ft to	25 ft From	E Dento	ft to	J Omer fr	From	ft. toft.	
		st source of possible conta	mination:		10. 00 1,		, 110111	11. 10	
☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☑ Other (specify below)									
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well									
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well ☐ Ditch									
Direction from well .West Distance from well .100'. FROM TO LITHOLOGIC LOG FROM TO LITHOL LOG (cont.) or PLUGGING INTERVALS									
FROM	TO		IC LOG	FROM	TO	LITHO. L	OG (cont.) or PL	UGGING INTERVALS	
5	5 9	no sample						···	
9	17	clay silty brown				1	HANNEL CONTROL OF THE PARTY OF		
17	26	sandy clay brown sand & gravel					and the second s		
26	29	silty clay brown					····		
29	40	silty clay gray			· · · · · · · · · · · · · · · · · · ·		· · · · · · · · · · · · · · · · · · ·	<u> </u>	
40	45	fine gravel unifrom			·			· · · · · · · · · · · · · · · · · · ·	
45	60	sand & gravel				 	**************************************		
60	68	gravel					······································	· · · · · · · · · · · · · · · · · · ·	
68	74	shale gray				<u> </u>			
7 CON'I	RACTO	DR'S OR LANDOWNER	S'S CERTIFICATION	N: This wat	er well	was 🖊 const	ructed, \square recons	tructed, or plugged	
under m	v inrisdia	ction and was completed o	n (mo/day/year) 04/29	9/2011 a	nd this r	ecord is true	to the best of my	knowledge and belief	

Check: White Copy, Blue Copy, Pink Copy