Pump test data: Well water was Pump test data: Well water was Est. Yield gpm: Well water was WELL WATER TO BE USED AS: 5 Public 1 Domestic 3 Feed lot 6 Oil field water s 2 Irrigation 4 Industrial 7 Domestic (lawn	Section Number 29 Township Number Range Number T 2 S R 17 E Global Positioning System (decimal degrees, min. of 4 digits) Latitude: N 39.95310° Longitude: W 95.53597° Elevation: RIM: 1137.46; TOC: 1137.24 Datum: NAVD 29 NAD 27 And Mallan (DRA) Data Collection Method: legal survey 5 ft. 2 ft. 3 ft. ft below land surface measured on mo/day/yr 4/11/14
2 WATER WELL OWNER: Patricia Bearce RR#, St. Address, Box # : 530 Oregon City, State, ZIP Code : Hiawatha, KS 66434 3 LOCATE WELL'S LOCATON WITH AN "X" IN SECTION BOX: N WELL'S STATIC WATER LEVEL 9.99 Pump test data: Well water was Est. Yield gpm: Well water was WELL WATER TO BE USED AS: 5 Public 1 Domestic 3 Feed lot 6 Oil field water s 2 Irrigation 4 Industrial 7 Domestic (lawn Was a chemical/bacteriological sample subm. Sample was submitted 5 TYPE OF CASING USED: 5 Wrought Iron 8 Cor 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Oth 2 PVC 4 ABS 7 Fiberglass Blank casing diameter 2 in. to 7.05 ft., Dia Casing height below land surface 0.22 ft., Weight TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) 1	Longitude: W 95.53597° Elevation: RIM: 1137.46; TOC: 1137.24 Datum: NAVD 29 NAD 27 pu didita (DRL) Data Collection Method: legal survey ft. MW5 ft. 2 ft. 3 ft. ft. below land surface measured on mo/day/yr 4/11/14
RR#, St. Address, Box # : 530 Oregon City, State, ZIP Code : Hiawatha, KS 66434 3 LOCATE WELL'S 4 DEPTH OF COMPLETED WELL 25.0 LOCATON WITH AN "X" IN SECTION BOX: N	Elevation: RIM: 1137.46; TOC: 1137.24 Datum: NAVD 29 NAD 27 pm differ (DR4) Data Collection Method: legal survey ft. MW5 ft. 2 ft. 3 ft. ft. below land surface measured on mo/day/yr 4/11/14
City, State, ZIP Code : Hiawatha, KS 66434 3 LOCATE WELL'S 4 DEPTH OF COMPLETED WELL 25.0 LOCATON WITH AN "X" IN SECTION BOX: N Depth(s) Groundwater Encountered 1 WELL'S STATIC WATER LEVEL 9.99 Pump test data: Well water was Est. Yield gpm: Well water was WELL WATER TO BE USED AS: 5 Public 1 Domestic 3 Feed lot 6 Oil field water s 2 Irrigation 4 Industrial 7 Domestic (lawn) Was a chemical/bacteriological sample submits ample was submitted 5 TYPE OF CASING USED: 5 Wrought Iron 8 Cor 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Oth 2 PVC 4 ABS 7 Fiberglass Blank casing diameter 2 in. to 7.05 ft., Dia Casing height below land surface 0.22 ft., Weight TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) 1	5 ft. MW5 ft. 2 ft. 3 ft. ft below land surface measured on mo/day/yr 4/11/14
LOCATON WITH AN "X" IN SECTION BOX: N Pump test data: Well water was Pump test data: Well water was Est. Yield gpm: Well water was WELL WATER TO BE USED AS: 5 Public 1 Domestic 3 Feed lot 6 Oil field water s 2 Irrigation 4 Industrial 7 Domestic (lawn Was a chemical/bacteriological sample submissample was submitted 5 TYPE OF CASING USED: 5 Wrought Iron 8 Cor 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Oth 2 PVC 4 ABS 7 Fiberglass Blank casing diameter 2 in. to 7.05 ft., Dia Casing height below land surface 0.22 ft., Weight TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) 1	MW5 ft. 2 ft. below land surface measured on mo/day/yr 4/11/14
WITH AN "X" IN SECTION BOX: N Pump test data: Well water was Pump test data: Well water was Est. Yield gpm: Well water was WELL WATER TO BE USED AS: 5 Public 1 Domestic 3 Feed lot 6 Oil field water s 2 Irrigation 4 Industrial 7 Domestic (lawn Was a chemical/bacteriological sample submissample was submitted 5 TYPE OF CASING USED: 5 Wrought Iron 8 Cor 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Oth 2 PVC 4 ABS 7 Fiberglass Blank casing diameter 2 in. to 7.05 ft., Dia Casing height below land surface 0.22 ft., Weight TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) 1	
Pump test data: Well water was Est. Yield gpm: Well water was WELL WATER TO BE USED AS: 5 Public 1 Domestic 3 Feed lot 6 Oil field water s 2 Irrigation 4 Industrial 7 Domestic (lawn Was a chemical/bacteriological sample submited 5 TYPE OF CASING USED: 5 Wrought Iron 8 Cor 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Oth (2) PVC 4 ABS 7 Fiberglass Blank casing diameter 2 in. to 7.05 ft., Dia Casing height below land surface 0.22 ft., Weight TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) 1	It. bolow land surface incusared of
WELL WATER TO BE USED AS: 3 Public WELL WATER TO BE USED AS: 3 Public I Domestic 3 Feed lot 6 Oil field water s 2 Irrigation 4 Industrial 7 Domestic (lawn Was a chemical/bacteriological sample submits Sample was submitted 5 TYPE OF CASING USED: 5 Wrought Iron 8 Cor 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Oth 2 PVC 4 ABS 7 Fiberglass Blank casing diameter 2 in. to 7.05 ft., Dia Casing height below land surface 0.22 ft., Weight TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) 1	ft. after hours pumping gpm
WELL WATER TO BE USED AS: 3 Public WELL WATER TO BE USED AS: 3 Public I Domestic 3 Feed lot 6 Oil field water s 2 Irrigation 4 Industrial 7 Domestic (lawn Was a chemical/bacteriological sample submits Sample was submitted 5 TYPE OF CASING USED: 5 Wrought Iron 8 Cor 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Oth 2 PVC 4 ABS 7 Fiberglass Blank casing diameter 2 in. to 7.05 ft., Dia Casing height below land surface 0.22 ft., Weight TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) 1	ft. after hours pumping gpm
Was a chemical/bacteriological sample submissample was submitted 5 TYPE OF CASING USED: 5 Wrought Iron 8 Cor 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Oth 2 PVC 4 ABS 7 Fiberglass Blank casing diameter 2 in. to 7.05 ft., Dia Casing height below land surface 0.22 ft., Weight TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) 1	
Was a chemical/bacteriological sample submission of Sample was submitted 5 TYPE OF CASING USED: 5 Wrought Iron 8 Cor 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Oth 2 PVC 4 ABS 7 Fiberglass Blank casing diameter 2 in. to 7.05 ft., Dia Casing height below land surface 0.22 ft., Weight TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) 1	upply 9 Dewatering 12 Other (Specify below)
S Sample was submitted Sample was submitt	itted to Department? Yes No X; If yes, mo/day/yrs
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Oth (2) PVC 4 ABS 7 Fiberglass Blank casing diameter 2 in. to 7.05 ft., Dia Casing height below land surface 0.22 ft., Weight TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) 1	water well Distillected? Tes No X
(2) PVC 4 ABS 7 Fiberglass Blank casing diameter 2 in. to 7.05 ft., Dia Casing height below land surface 0.22 ft., Weight TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) 1	crete tile CASING JOINTS: Glued Clamped
2 Brass 4 Galvanized steel 6 Concrete tile 8 RW (SR)	Threaded X
2 Brass 4 Galvanized steel 6 Concrete tile 8 RW (SR)	in. to ft., Dia in. to ft.
2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR)	lbs./ft. Wall thickness or gauge No.
2 Brass 4 Galvanized steel 6 Concrete tile 8 RW (SR)	9 ABS 11 Other (specify)
SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauze wrapped 7 T 2 Louvered shutter 4 Key punched 6 Wire wrapped 8 S SCREEN-PERFORATED INTERVALS: From 7.05 ft. to From ft. to GRAVEL PACK INTERVALS: From 5 ft. to GRAVEL PACK INTERVALS: From 5 ft. to	0 Asbestos-Cement 12 None used (open hole)
1 Continuous slot (3)Mill slot 5 Gauze wrapped 7 I 2 Louvered shutter 4 Key punched 6 Wire wrapped 8 S SCREEN-PERFORATED INTERVALS: From 7.05 ft. to GRAVEL PACK INTERVALS: From 5 ft. to	Corch out 9 Drilled holes 11 None (open hole)
SCREEN-PERFORATED INTERVALS: From 7.05 ft. to From ft. to GRAVEL PACK INTERVALS: From 5 ft. to	aw Cut 10 Other (specify)
From ft. to GRAVEL PACK INTERVALS: From 5 ft. to	25.05 ft. From ft. to ft.
GRAVEL PACK INTERVALS: From 5 ft. to	ft. From ft. to ft.
	25.35 ft. From n. to n.
From tt. to	n. From n. w
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3B	entonite (4)Other Concrete: 0-1 ft
Grout Intervals From 1 ft. to 5 ft. From	ft. to tt. From tt.
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fue 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fer	vestock pens 13 Insecticide Storage 16 Other (specify lel storage 14 Abandoned water well below) tilizer storage 15 Oil well/ gas well many feet? ~50 ft
	OM TO PLUGGING INTERVALS
0 25.35 Concrete & brick on top; Brown silty clay	
	Flushmount waiver from BOW
by (s	ell Record was completed on (anorday/year) 4/14/14 signature)
INSTRUCTIONS: Please fill in blanks or circle the correct answers. Send top three concerns of the concerns of	