


1 LOCATION OF WATER WELL: County: Brown Fraction: SW 1/4 NE 1/4 NW 1/4 Section Number: 29 Township Number: T 2 S Range Number: R 17 EW

Distance and direction from nearest town or city street address of well if located within city? in town MW6

2 WATER WELL OWNER: Brown County Cooperative RR#, St. Address, Box #: 900 Oregon Board of Agriculture, Division of Water Resources City, State, ZIP Code: Hiawatha, KS. Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  4 DEPTH OF COMPLETED WELL: 12.5 ft. ELEVATION: 4.20 ft. below land surface measured on mo/day/yr

Depth(s) Groundwater Encountered: 1. 4.20 ft. 2. 12.5 ft. 3. 12.5 ft.

WELL'S STATIC WATER LEVEL: 4.20 ft. below land surface measured on mo/day/yr

Pump test data: Well water was 4.20 ft. after 12.5 hours pumping 12.5 gpm

Est. Yield 12.5 gpm: Well water was 4.20 ft. after 12.5 hours pumping 12.5 gpm

Bore Hole Diameter: 2.0 in. to 2.0 ft., and 2.0 in. to 2.0 ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted No

Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Welded Clamped Threaded
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below)

Blank casing diameter: 2.0 in. to 2.0 ft., Dia. 2.0 in. to 2.0 ft., Dia. 2.0 in. to 2.0 ft.

Casing height above land surface: 0 in., weight 0 lbs./ft. Wall thickness or gauge No. 2

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 2 PVC 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 2.5 ft. to 12.5 ft., From 2.5 ft. to 12.5 ft., From 2.5 ft. to 12.5 ft.

GRAVEL PACK INTERVALS: From 2.0 ft. to 12.5 ft., From 2.0 ft. to 12.5 ft., From 2.0 ft. to 12.5 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 0 ft. to 1.0 ft., From 1.0 ft. to 2.0 ft., From 2.0 ft. to 12.5 ft.

What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
13 Insecticide storage

Direction from well? 0 How many feet?

| FROM | TO | LITHOLOGIC LOG | FROM | TO | PLUGGING INTERVALS |
|------|------|--|------|----|--------------------|
| 0 | .50 | GRAVEL clay, highly plastic, soft black, fill, damp clay, highly plastic MODERATE brown hard, moist | | | |
| .50 | 4.0 | | | | |
| 4.0 | 12.5 | | | | |

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-14-94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 4398 This Water Well Record was completed on (mo/day/yr) 7/15/94 under the business name of Kansas City Testing Lab Inc. by (signature) John Brueggeman