Patton 11-01

WATER WELL RECORD	Form WWC-5	Division of Water Resources App	p. No.
1 LOCATION OF WATER WELL: County: Brown	Fraction NW ¼ SW ¼ SW ¼ NW ¼	Section Number Township No. 6 T 2	o. Range Number R 18
Street/Rural Address of Well Location; if unknown, distance & direction Global Positioning System (GPS) information:			S) information:
from nearest town or intersection: If at owner's address, check here .		Latitude:39.9080830	(in decimal degrees)
1/3 mile south of 280th St & plumtree Rd		Longitude: -95.4517500 (in decimal degrees)	
,		Elevation:	<u></u>
2 WATER WELL OWNER: Ryan Patton		<u>Datum</u> :	. ∐ NAD 27
RR#, Street Address, Box #: 1974 260th St		GPS unit (Make/Model: Garmin 12xl	
City, State, ZIP Code : Hiawatha, KS 66434		Digital Map/Photo, Topographic Map, Land Survey	
niawau	ia, NS 00454	Est. Accuracy: \square <3 m, \square 3-5 m,	☐ 5-15 m, ☐ >15 m
3 LOCATE WELL 90			
	10		
SECTION BOX: Depth(s) Ground	WELL'S STATIC WATER LEVEL43ft. below land surface measured on mo/day/yr		
	Pump test data: Well water wasft. after hours pumping		
	EST VIELD 75 cmm Well water was the other house numerical		
NW ND			
W E Bore Hole Diameter 1.5			
Domestic D Feedlet D Oil field water supply Developing D Other (Specify below)			
SW SE			
Was a chemical/bacteriological sample submitted to Department? ☐ Yes ☑ No			
S If yes, mo/day/yr sample was submitted			
mile Water well disinfected? ☑ Yes □ No			
5 TYPE OF CASING USED: Steel V PVC Other			
CASING JOINTS: ☑ Glued ☐ Clamped ☐ Welded ☐ Threaded			
Casing diameter .8 in. to .89 ft., Diameter in. to ft., Diameter ft.			
Casing height above land surface. 24 in., Weight 7.07lbs./ft., Wall thickness or gauge No0.41"			
TYPE OF SCREEN OR PERFORATION MATERIAL:			
☐ Steel ☐ Stainless Steel			
☐ Brass ☐ Galvanized Steel ☐ None used (open hole) SCREEN OR PERFORATION OPENINGS ARE:			
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)			
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)			
SCREEN-PERFORATED INTERVALS: From			
From			
GRAVEL PACK INTERVALS: From			
From			
6 GROUT MATERIAL: ☐ Neat cement ☐ Cement grout ☐ Bentonite ☐ Other			
Grout Intervals: From .5			
What is the nearest source of possible contamination: ☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☑ Other (specify below)			
Septic tank Lateral ling Sewer lines Cesspool		☐ Abandoned water well	
Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well Road			
Direction from well .West	Distance	rom well40'	
FROM TO LITHOLOG	GIC LOG FROM	TO LITHO. LOG (cont.) or	PLUGGING INTERVALS
0 4 no sample			
4 11 clay silty brown			
11 21 clay sandy brown			
21 30 clay gray			
30 43 clay sandy brown			
43 83 sand VF brown			
83 88 gravel			
88 89 shale olive			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ✓ constructed, ☐ reconstructed, or ☐ plugged			
under my jurisdiction and was completed on (mo/day/year) .05/06/20.11 and this record is true to the best of my/knowledge and belief.			
Kansas Water Well Contractor's License No7.79 This Water Well Record was completed on (mo/day/year) .05/23/2011			
under the business name of Drill-Well, LLC			
INSTRUCTIONS: Use typewriter or hall point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send three copies			
(white blue pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St. Suite 420, Topeka, Kansas 66612-1367.			
Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell/index.html.			
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy			