

USE TYPEWRITER OR BALL
POINT PEN—PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:		County DONIPHAN	Fraction NW NE SE 1/4 SE 1/4 SE 1/4	Section number 24	Township number T 2	Range number S 19	E/W E/W
2. Distance and direction from nearest town or city: 1 1/2 E - 1/4 N.				3. Owner of well: Rubink Farms Inc.			
Street address of well location if in city: Highland, KS.				R.R. or street: City, state, zip code: Highland KS 66035			
4. Locate with "X" in section below:		Sketch map:		6. Bore hole dia. 10 in. Completion date 6-15-76			
				7. Cable tool <input type="checkbox"/> Rotary <input checked="" type="checkbox"/> Driven <input type="checkbox"/> Dug Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input type="checkbox"/> Reverse rotary			
5. Type and color of material		From		To		8. Use: <input checked="" type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input checked="" type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other	
Brown Sandy Clay		0		4		9. Casing: Material PVC Height: Above or below Threaded <input type="checkbox"/> Welded <input type="checkbox"/> Surface 24 in. RMP <input type="checkbox"/> PVC 614C Weight 2.75 lbs./ft. Dia. 5 in. to 53 ft. depth Wall Thickness: inches or Dia. <input type="checkbox"/> in. to <input type="checkbox"/> ft. depth gage No. 258	
Gray Silt		4		9		10. Screen: Manufacturer's name Pumco	
Brown Sandy Clay		9		15		Type PVC Dia. 5" Slot/gauze 0.25 Length 30 Set between 15 ft. and 35 ft. 45 ft. and 55 ft.	
" " " Med. Gravel		15		19		Gravel pack? <input checked="" type="checkbox"/> Size range of material 0.30, 0.60	
Fine, Med Brown Gravel		19		24		11. Static water level: 1' over Cas mo./day/yr. ft. below land surface Date 2-6-76	
Fine Gray Sand		24		26		12. Pumping level below land surfaces: Air test ft. after <input type="checkbox"/> hrs. pumping <input type="checkbox"/> g.p.m. ft. after <input type="checkbox"/> hrs. pumping <input type="checkbox"/> g.p.m. Estimated maximum yield 30 g.p.m.	
Med. Pea Gravel		26		35		13. Water sample submitted: <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Date	
Fine Sand & Clay		35		45		14. Well head completion: Pitless adapter 24 Inches above grade	
Med. Pea Gravel		45		55		15. Well grouted? <input checked="" type="checkbox"/> With: <input type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input checked="" type="checkbox"/> Concrete Depth: From 0 ft. to 10 ft.	
						16. Nearest source of possible contamination: ft. 1000 Direction N Type Lagoon Well disinfected upon completion? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	
						17. Pump: <input checked="" type="checkbox"/> Not installed Manufacturer's name Model number <input type="checkbox"/> HP <input type="checkbox"/> Volts Length of drop pipe <input type="checkbox"/> ft. capacity <input type="checkbox"/> g.p.m. Type: <input type="checkbox"/> Submersible <input type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other	
18. Elevation: 980 Rm Topography: <input type="checkbox"/> Hill <input checked="" type="checkbox"/> Slope <input type="checkbox"/> Upland <input type="checkbox"/> Valley		19. Remarks: I WILL PUT THE CEMENT SLAB AROUND THE WELL MY SELF H. James Rubink		20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. STEADER DRUG CO INC 182 Business name License No. Address RT 1 Holton Kansas Signed Dale Bohra Date 6-18- Authorized representative			