

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Doniphan	S 1/2 NE 1/4 1/4	19	T 2 S	R 19 E/W

Distance and direction from nearest town or city street address of well if located within city?

3 miles West - 3/4 mile North - - on West side of road -- from Highland, KS

Top of hill

2 WATER WELL OWNER:	Wm. R. Gordon	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # :	12020 N 118th St.	Application Number:
City, State, ZIP Code :	Scottsdale, AZ 85259-3218	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 58 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. 8 ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL (8') ft. below land surface measured on mo/day/yr 4-6-98
	Pump test data: Well water was ft. after hours pumping gpm
	Est. Yield gpm: Well water was ft. after hours pumping gpm
	Bore Hole Diameter in. to ft. and in. to ft.
WELL WATER TO BE USED AS:	
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well	
Was a chemical/bacteriological sample submitted to Department? Yes.....No.....; If yes, mo/day/yr sample was submitted	
Water Well Disinfected? Yes X No	

5 TYPE OF BLANK CASING USED:	3 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	XX Clay pipe joints
Blank casing diameter 10 in. to ft. Dia	in. to ft. Dia	in. to ft. Dia	in. to ft. Dia
Casing height above land surface in., weight	lbs./ft. Wall thickness or gauge No.		
TYPE OF SCREEN OR PERFORATION MATERIAL:			
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:			
1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes
7 Torch cut 10 Other (specify)			
SCREEN-PERFORATED INTERVALS: From ft. to ft. From ft. to ft. From ft. to ft. From ft. to ft.			
Sand and gravel PACK INTERVALS: From 58 ft. to 50 ft. From 50 ft. to 6 ft. From 5 ft. to field level			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	XX 3 Bentonite	4 Other
Grout Intervals: From 6 ft. to 5 ft. From ft. to ft. From ft. to ft. From ft. to ft.				
What is the nearest source of possible contamination: (capped & covered) XX 10 Livestock pens 14 Abandoned water well				
1 Septic tank	4 Lateral lines	7 Pit privy	11 Fuel storage	15 Oil well/Gas well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	16 Other (specify below)
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	13 Insecticide storage	
Direction from well? South & slightly East How many feet? 3420				

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
		Removed pump jack & pump - plugged			
		No longer needed			
		By Mike Holt & Francis Gordon			
		Forms & recommendations by Brown Co. Agricultural Agent			
		①			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged and this record is true to the best of my knowledge and belief. Kansas
completed on (mo/day/year) 4-11-98
Water Well Contractor's License No. This Water Well Record was completed on (mo/day/yr) 4-13-98
under the business name of Francis Gordon LPA by (signature) Francis Gordon