

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Doniphan		SW 1/4 SW 1/4 NE 1/4	24	T 2 S	R 21 E
Distance and direction from nearest town or city street address of well if located within city? 1/2 West and 5 1/2 North of Blair, Ks.					
2 WATER WELL OWNER: Daryl Wyatt					
RR#, St. Address, Box # :		Box 68	Board of Agriculture, Division of Water Resources		
City, State, ZIP Code :		Wathena, Kansas 66090	Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 40 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 10' ft. below land surface measured on mo/day/yr 7-26-95			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield 5 gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter in. to ft., and in. to ft.			
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes X No			
5 TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued X Clamped
2 PVC		4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded
			7 Fiberglass		Threaded
Blank casing diameter 5 in. to 0-12 ft., Dia 5 in. to 32-40 ft., Dia in. to ft.					
Casing height above land surface 24 in., weight 258 lbs./ft. Wall thickness or gauge No. 2.82					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel		3 Stainless steel	5 Fiberglass	7 PVC	10 Asbestos-cement
2 Brass		4 Galvanized steel	6 Concrete tile	8 RMP (SR)	11 Other (specify)
				9 ABS	12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot		3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter		4 Key punched	6 Wire wrapped	9 Drilled holes	
			7 Torch cut	10 Other (specify)	
SCREEN-PERFORATED INTERVALS: From 12' ft. to 32' ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 10' ft. to 32' ft., From ft. to ft.					
6 GROUT MATERIAL:					
1 Neat cement		2 Cement grout	3 Bentonite	4 Other	
Grout Intervals: From 0 ft. to 10 ft., From ft. to ft., From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank		4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines		5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines		6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
				13 Insecticide storage	Creek
Direction from well? West		How many feet? 50'			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1	Top soil			
1	10	brown clay			
10	14	cherty limestone, loose			
14	25	grey shle.			
25	26	grey L.S.			
26	28	grey sh.			
28	40	grey L.S.			
* Note: 7-28-95 Permission to shallow grout from Don Taylor					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-26-95 and this record is true to the best of my knowledge and belief. Kansas					
Water Well Contractor's License No. 182		This Water Well Record was completed on (mo/day/yr) 9-6-95			
under the business name of Strader Drilling Co., Inc.		by (signature) Dale Skren			
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					