

1 LOCATION OF WATER WELL: County: Washington	Fraction: NE ¼ NE ¼ SE ¼	Section Number: 8	Township Number: T 2 S	Range Number: R 5 (E)W
---	---------------------------------	--------------------------	-------------------------------	-------------------------------

Distance and direction from nearest town or city street address of well if located within city?
605 W. North St.

2 WATER WELL OWNER: **David Eldean**
 RR#, St. Address, Box # : **605 W. North St.**
 City, State, ZIP Code : **Hanover, KS. 66945**
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL 58 ft. ELEVATION:
--	--

AN "X" IN SECTION BOX:

N
---NW---NE---
W E
---SW---SE---
S

Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft.

WELL'S STATIC WATER LEVEL **35** ft. below land surface measured on mo/day/yr **10/27/03**

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield **5.0** gpm: Well water was ft. after hours pumping gpm

WELL WATER TO BE USED AS:

1 Domestic	3 Feedlot	5 Public water supply	8 Air conditioning	11 Injection well
2 Irrigation	4 Industrial	6 Oil field water supply	9 Dewatering	12 Other (Specify below)
		7 Domestic (lawn & garden)	10 Monitoring well	Lawn & Garden

Was a chemical/bacteriological sample submitted to Department? Yes No *; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes * No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued * Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Welded
			Threaded
Blank casing diameter 5 in. to 38 ft., Dia			
Casing height above land surface 18 in., weight 200 lbs./ft. Wall thickness or guage No. .265			
TYPE OF SCREEN OR PERFORATION MATERIAL:			
1 Steel	3 Stainless Steel	5 Fiberglass	7 PVC
2 Brass	4 Galvanized Steel	6 Concrete tile	8 RMP (SR)
			9 ABS
			10 Asbestos-Cement
			11 Other (Specify)
			12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:			
1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes
		7 Torch cut	10 Other (specify)
			11 None (open hole)
SCREEN-PERFORATED INTERVALS: From 38 ft. to 58 ft.			
GRAVEL PACK INTERVALS: From 30 ft. to 58 ft.			

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From **5** ft. to **30** ft.

What is the nearest source of possible contamination:

1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	

Direction from well? **None Present** How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Topsoil			
2	36	Brown Clay (Silty)			
36	41	Sand (Fine/Yellow)			
41	58	Sand (Med.-Course/Yellow)			
58	62	Limestone & Shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) **10/27/03** and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No **518** This Water Well Record was completed on (mo/day/yr) **10/30/03** under the business name of **Blue Valley Drilling** by (signature) *Ein Steuber*