

1 LOCATION OF WATER WELL:		Fraction	Section Number		Township Number		Range Number	
County: Marshall		NW ¼ SW ¼ SW ¼	12		T 02 S		R 06 W	
Distance and direction from nearest town or city street address of well if located within city? 875 6 th Road, Marysville, KS (South of unincorporated town of Herkimer)								
2 WATER WELL OWNER:		Southeast Nebraska Cooperative						
RR#, St. Address, Box # :		403 S. 3 rd Street						
City, State, ZIP Code :		Beatrice, NE 68310						
		Board of Agriculture, Division of Water Resources						
		Application Number:						
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 33 ft. ELEVATION: 1205.12 (TOC)						
		Depth(s) Groundwater Encountered 1 30 ft. 2 ft. 3 ft.						
		WELL'S STATIC WATER LEVEL 32.4 ft. below land surface measured on mo/day/yr 6-16-05						
		Pump test data: Well water was ft. after hours pumping gpm						
		Est. Yield gpm Well water was ft. after hours pumping gpm						
		Bore Hole Diameter 8.5 in. to 35 ft. and in. to ft.						
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well						
		1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)						
		2 Irrigation 4 Industrial 7 Lawn and garden (domestic) 10 Monitoring well						
		Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted						
		Water Well Disinfected? Yes No X						
5 TYPE OF BLANK CASING USED:		5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped						
1 Steel 3 RMP (SR)		6 Asbestos-Cement 9 Other (specify below) Welded						
2 PVC 4 ABS		7 Fiberglass Threaded Flush						
Blank casing diameter 2 in. to ft., Dia in. to ft., Dia in. to ft., Dia								
Casing height above land surface Flushmount in., weight 0.703 lbs./ft. Wall thickness or gauge No. Sch. 40								
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement						
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)								
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)								
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)						
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes								
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)								
SCREEN-PERFORATED INTERVALS: From 13 ft. to 33 ft. From ft. to ft.								
GRAVEL PACK INTERVALS: From 10 ft. to 33 ft. From ft. to ft.								
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other								
Grout Intervals From 0.5 ft. to 10 ft. From ft. to ft. From ft. to ft.								
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well						
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/ Gas well								
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)								
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage								
Direction from well?		How many feet?						
FROM	TO	CODE	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS		
0	14.5		Silty clay					
14.5	19.5		Shale with thin limestone layers					
19.5	22		Limestone, shaley in part					
22	35		Shale with thin limestone layers					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/yr) 6-16-05 and this record is true to the best of my knowledge and belief. Kansas								
Water Well Contractor's License No. 531				This Water Well Report was completed on (mo/day/yr) 7-6-05				
under the business name of Geotechnical Services, Inc.				by (signature)				
INSTRUCTIONS: Please fill in blanks and circle the correct answers. Send three copies to Kansas Department of Health and Environment, Bureau of Water, 1000 S W Jackson St., Ste. 420, Topeka, Kansas 66612-1367. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.								

OFFICE USE ONLY

1

२

SEC