

1 LOCATION OF WATER WELL: County: Marshall Fraction: NE 1/4 SE 1/4 NW 1/4 Section Number: 33 Township Number: T 2 S Range Number: R 7 EW

Distance and direction from nearest town or city street address of well if located within city? 401 Walnut Street

2 WATER WELL OWNER: Claude Hittle RR#, St. Address, Box #: 401 Walnut City, State, ZIP Code: Marysville, Ks. Board of Agriculture, Division of Water Resources Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram of section box with 'X' in NW corner] 4 DEPTH OF COMPLETED WELL: 37 ft. ELEVATION: WELL'S STATIC WATER LEVEL: 25 ft. below land surface measured on mo/day/yr April 16, 1990

5 TYPE OF BLANK CASING USED: 1 Steel 2 PVC 3 RMP (SR) 4 ABS 5 Wrought iron 6 Asbestos-Cement 7 Fiberglass 8 Concrete tile 9 Other (specify below) 10 Asbestos-cement CASING JOINTS: Glued X Clamped Welded Threaded Blank casing diameter: 5 in. to ft. Dia. in. to ft. Dia. in. to ft. Casing height above land surface: 18 in., weight 200 lbs./ft. Wall thickness or gauge No. TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 2 Brass 3 Stainless steel 4 Galvanized steel 5 Fiberglass 6 Concrete tile 7 PVC 8 RMP (SR) 9 ABS 10 Other (specify) 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Louvered shutter 3 Mill slot 4 Key punched 5 Gauzed wrapped 6 Wire wrapped 7 Torch cut 8 Saw cut 9 Drilled holes 10 Other (specify) 11 None (open hole) SCREEN-PERFORATED INTERVALS: From 17 ft. to 37 ft. GRAVEL PACK INTERVALS: From 17 ft. to 37 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 0 ft. to 17 ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 2 Sewer lines 3 Watertight sewer lines 4 Lateral lines 5 Cess pool 6 Seepage pit 7 Pit privy 8 Sewage lagoon 9 Feedyard 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below) Direction from well? Northeast How many feet? 60

Table with columns: FROM, TO, LITHOLOGIC LOG, FROM, TO, PLUGGING INTERVALS. Rows include: 0-28 Topsoil, 28-30 Blue clay, 30-36 Med-Corse Sand, 36-40 Limestone.

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) April 16, 1990 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 518 This Water Well Record was completed on (mo/day/yr) April 16, 1990 under the business name of Blue Valley Drilling by (signature) Eric [unclear]