WATER WELL RECORD Form WWC-5 KSA 82a-1212 1 LOCATION OF WATER WELL: FRACTION SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER Sumner SW1/4 \mathbf{SW} 1/4 SE 1/4 Т 30 s R 1E Ε/W Distance and direction from nearest town or city street address of well if located within city? 1 mile So. of 119th S. & 1/2 mile East, No. side of Hwy 81 DONDLINGER & SONS CONSTRUCTION WATER WELL OWNER: Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX #: P.O. Box 398 20110210 Wichita, Kansas CITY, STATE: Application Number: ZIP CODE 4 DEPTH OF COMPLETED WELL: 40 ft **ELEVATION:** LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: ft. ft. ft. Depth of groundwater Encountered: N WELL'S STATIC WATER LEVEL FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 6/1/11 Well water was Pump test data: ft. after hours of pumping @ gpm -NW NE-Mile Est. Yield: gpm Well water was ft. after hours of pumping @ apm Bore Hole Diameter 12 and ft WELL WATER TO BE USED AS: 9. Dewatering 11. Injection well SW SE 7. Lawn and garden only 1. Domestic 5. Public water supply 12. Other (Specify below) 10. Monitoring well 2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO) (YES) submitted Was Water Well Disinfected? NO 5 TYPE OF CASING USED: 9. Other (Specify below) CASING JOINTS: Glued Threaded 7. Fiberglass 5. Wrought Iron 3. RPM (SR) 1. Steel Welded Clamped SDR-26 8. Concrete tile 6. Asbestos-Cement 4. ABS 2. PVC 8 20 ft. Dia. ft... Dia Blank casing diameter to to in to ft 12 Weight: 5.52 Casing height above land surface: lbs. / ft. Wall thickness or gauge No. .332 TYPE OF SCREEN OR PERFORATION MATERIAL: 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify) 1. Steel 8. RMP (SR) 12. None used (open hole) 2. Brass 4. Galvanized Concrete Tile 10. Asbestos-Cement SCREEN OR PERFORATION OPENINGS ARE: 3. Mill slot 9. Drilled holes 11. None (open hole) 1. Continuous slot 5. Gauzed wrapped 7. Torch cut 2. Louvered shutter 6. Wire wrapped 8. Saw cut 10. Other (specify) 4. Key punched SCREEN - PERFORATION INTERVAL 20 From to 40 ft. From ft. ft. From ft. to ft.. From ft. to ft. 20 **GRAVEL PACK INTERVALS:** to 40 From ft.. From ft to ft. ft. From to ft., From to ft. **GROUT MATERIALS:** 6 2. Cement Grout Other bentonite hole plug 1. Neat cement 3. Bentonite Grout Intervals: 0 ft. 20 From ft.. From ft. to ft., From ft. What is the nearest source of possible contamination: 10. Livestock pens 7. Pit privy 13. Insecticide storage 15. Oil well/Gas well 1. Septic tank 4. Lateral lines 16. Other (specify below) 11. Fuel storage 8. Sewage lagoon 14. Abandon water well 2. Sewer lines 5. Cess Pool None Apparent 9. Feed yard 12. Fertilizer storage 6. Seepage pit 3. Watertight sewer line Direction from well? How many feet? From LITHOLOGIC LOG From To LITHOLOGIC LOG Τо 0 topsoil 3 14 clay 14 18 sandy clay 18 24 fine sand 24 36 medium sand 36 40 gray shale Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed 3. plugged under my jurisdiction and

6/1/2011 was completed on (mo/day/year) and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 6/6/2011 Todd S. Harb under the business name of Harp Well and Pump Service by (signature)