


1 LOCATION OF WATER WELL: Sumner	FRACTION SW 1/4 SE 1/4 SE 1/4	Section Number 4	Township Number T 30 S	Range Number R 1E E/W
--	---	----------------------------	----------------------------------	---------------------------------

Distance and direction from nearest town or city street address of well if located within city?

1m S. of 119th S., 1/4 W. of Hydraulic, 1/8 N., (Lot 8 Block C) Peck, Ks.

2 WATER WELL OWNER: OHRT, Timothy	Board of Agriculture, Division of Water Resource	Application Number: 67120
RR#, ST. ADDRESS, BOX #: RR #1 Box 338	CITY, STATE, ZIP CODE: Peck, Kansas 67120	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL 30 ft. ELEVATION: Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft. ft. WELL'S STATIC WATER LEVEL 14 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr 12/29/1993 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 12 in. to 30 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No <input checked="" type="checkbox"/> ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <input checked="" type="checkbox"/> No
--	---

5 TYPE OF CASING USED: 1 Steel 3 RMP (SR) 2 PVC 4 ABS Blank casing Diameter 5 in. to 23 ft., Dia in. to ft. Casing height above land surface 12 in., weight 2.35 lbs./ft. Wall thickness or gauge No. .214	5 Wrought iron 6 Asbestos-Cement 7 Fiberglass SDR-26 8 Concrete tile 9 Other (Specify below) CASING JOINTS: Glued <input checked="" type="checkbox"/> Clamped Welded Threaded	TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 2 Brass 4 Galvanized steel 5 Fiberglass 6 Concrete tile 8 RMP (SR) 9 ABS 11 other (specify) 12 None used (open hole)
SCREEN OR PERFORATION OPENING ARE: 1 Continuous slot 3 Mill slot 2 Louvered shutter 4 Key punched SCREEN-PERFORATION INTERVALS: from 23 ft. to 30 ft., From ft. to ft. GRAVEL PACK INTERVALS: from 23 ft. to 30 ft., From ft. to ft.	5 Gauzed wrapped 6 Wire wrapped 7 Torch cut 8 Saw cut 9 Drilled holes 10 Other (specify)	8 Saw cut 11 None (open hole)

6 GROUT MATERIAL: 1 Neat cement Grout Intervals: From 3 ft. to 23 ft. From ft. to ft.	2 Cement grout 3 Bentonite 4 Other	10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage 14 Abandon water well 15 Oil well/Gas well 16 Other (specify below) None Apparent
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 2 Sewer lines 5 Cess pool 3 Watertight sewer lines 6 Seepage pit 7 Pit privy 8 Sewage lagoon 9 Feedyard		
Direction from well?		How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	topsoil			SEPTIC SYSTEM NOT INSTALLED AT THIS TIME
3	11	clay			
11	25	fine sand			
25	30	grey shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12/29/1993 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 12/31/93	Under the business name of Harp Well & Pump by (signature) <i>Jane Frederick</i>
--	--