## WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

	16	T		6		Transition /	I 9 1	٦	
1. Location of well:	County	Fraction		Section number		Township number	Range number		
1. Localion of well:	Sumner	1/4 NE 1/4 NE	1/4	- 5		T30 s	R 1E E/W	4	
2. Distance and dire	ction from nearest town or city:	T	1	er of well		erry Crow			
Street address of well location if in city: 12085 Estate Lane Peck, Kansas City, stat					337 Eule				
	Peck,		City, st	ate, zip c	ode: W	ichita, Kansas		$\dashv$	
4. Locate with "X" in section below: Sketch map:  N						6. Bore hole dia. 11 in. Well depth 60 ft.	8-11-78		
· · · · · · · · · · · · · · · · · · ·					ŀ	7 Cable tool X Rotary		1	
W NE -   E						Bored Reverse rotary  8. Use: X Domestic Public supply Industry Irrigation Air conditioning Stock Lawn Oil field water Other			
sw	SE				ŀ	9. Casing: MateStyrene		$\forall$	
						Threaded Weldedg1  Surface12" in.			
S						RMP_X PVC		۱٠	
	ile ————————————————————————————————————			Τ. Τ		Dia. 5 in. to 60 ft. dep	th!Wall Thickness: inches or		
5. Type and color of	material			From	То	10. Screen: Manufacturer's n	ame		
Topsoi1				0	3	Sunflower	olastic	-	
100011	-					Type styrene Slot/kd/de .06	_ Via. <del></del>	-	
Clay				3	12	Set between 40	ft. and <u>60</u> fi		
Fine sand with clay balls			12	35	Gravel pack? <u>ye</u> size ra	ndf	1.		
1210 5414 1201 5225									
Medium	to Coarse sand			35	60	11. Static water level:	face Date 8-11-78	_	
						12. Pumping level below land			
						ft. after h	, , -		
<u> </u>						Estimated maximum yield		- 1	
						13. Water sample submitted:	mo./day/yı		
							Date	4	
						14. Well head completion: X Pitless adapter	L2 Inches above grade		
						15. Well grouted? yes 1.		X	
						With: Neat cement	Bentonite _X Concrete		
					$\dashv$	Depth: From 4011 ft. to		$\dashv$	
						16. Nearest source of possible ft Direction	contamination: Type None		
					ļ	Well disinfected upon comple		10	
						17. Pump:	Not installed a-rite	-	
						Manufacturer's name Strandom Model number 20 Serie	es <sub>HP</sub> ½ volts 230		
						Length of drop pipe 45	_ ft. capacity20 g.p.m		
						Type: X Submersible	Turbine		
						Jet	Reciprocating		
	(Use a second	sheet if needed)				Centrifugal	Other	┙	
18. Elevation:	9. Remarks:					20. Water well contractor's o			
	Flat ground						This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.		
Topography:	*	eptic system not installed at this time				Harp Well & :	Pump 236	_	
Hill No apparent souree for contamination					Business name Wichita,	Kansas 67209	·-		
Slope Upland						Address	nold	_	
Valley						Signed Authorized rep	resentative 2 30-7	<u> </u>	
orward the white. blu	ue and pink copies to the Department	t of Health and Environment					Form WWC-5		