


LOCATION OF WATER WELL: Fraction NE 1/4 NE 1/4 NE 1/4 Section Number 17 Township Number T 30 S Range Number R 1 E/W  
 Distance and direction from nearest town or city street address of well if located within city?  
2 miles south of 81 Highway of Sedg & Sumner Co line.  
 WATER WELL OWNER: McAllister Drilling Board of Agriculture, Division of Water Resources  
 St. Address, Box #: 251 No Water Application Number:  
 City, State, ZIP Code: Wichita, KS 67209

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  
  
 DEPTH OF COMPLETED WELL: 29 ft. ELEVATION:  
 Depth(s) Groundwater Encountered 1. 13 ft. 2. ft. 3. ft.  
 WELL'S STATIC WATER LEVEL: 13 ft. below land surface measured on mo/day/yr 4-7-83  
 Pump test data: Well water was 14 ft. after 1/2 hours pumping 20 gpm  
 Est. Yield 50 gpm: Well water was ft. after hours pumping gpm  
 Bore Hole Diameter: 1.1 in. to 2.9 ft., and in. to ft.  
 WELL WATER TO BE USED AS:  
 5 Public water supply 8 Air conditioning 11 Injection well  
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)  
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well  
 Was a chemical/bacteriological sample submitted to Department? Yes.....No.....X.....; If yes, mo/day/yr sample was submitted  
 Water Well Disinfected? Yes X No

TYPE OF BLANK CASING USED:  
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped:  
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded:  
 7 Fiberglass Threaded:  
 Casing diameter: 5 in. to 1.9 ft. Dia. in. to ft. Dia. in. to ft. Dia. in. to ft.  
 Casing height above land surface: 12 in., weight 1.59 lbs./ft. Wall thickness or gauge No. 5 DR-26  
 TYPE OF SCREEN OR PERFORATION MATERIAL:  
 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement  
 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)  
 9 ABS 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:  
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)  
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes  
 7 Torch cut 10 Other (specify)  
 SCREEN-PERFORATED INTERVALS: From 19 ft. to 29 ft., From ft. to ft.  
 From ft. to ft., From ft. to ft.  
 GRAVEL PACK INTERVALS: From 15 ft. to 29 ft., From ft. to ft.  
 From ft. to ft., From ft. to ft.

GROUT MATERIAL:  
 1 Neat cement 2 Cement grout 3 Bentonite 4 Other  
 Grout intervals: From 10 ft. to 15 ft., From ft. to ft., From ft. to ft.  
 What is the nearest source of possible contamination:  
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well  
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well  
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)  
 13 Insecticide storage to be drilled  
 Direction from well? NE How many feet? NE 80 FT

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
2	2	top soil			
2	12	clay			
2	29	fine to med sand			

RECEIVED  
 JUN 10 1985  
 BUREAU OF OIL FIELD & ENVIRONMENTAL GEOLOGY

CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-7-83 and this record is true to the best of my knowledge and belief. Kansas Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) \_\_\_\_\_ for the business name of \_\_\_\_\_ by (signature) \_\_\_\_\_  
 INSTRUCTIONS. Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.