


1 LOCATION OF WATER WELL: County: SUMNER Fraction: NE 1/4 SE 1/4 SE 1/4 Section Number: 32 Township Number: T 30 S Range Number: R 1 E

Distance and direction from nearest town or city street address of well if located within city?
2 MI WEST OF BELLE PLAIN KS

2 WATER WELL OWNER: EARLINE HOGUE 67216
 RR#, St. Address, Box #: 2527 ELLIS WILHITA KS
 City, State, ZIP Code: 2527 ELLIS WILHITA KS
 Board of Agriculture, Division of Water Resources
 Application Number: NONE

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 40 ft. ELEVATION: 13.00
 Depth(s) Groundwater Encountered 1. 25 ft. 2. 25 ft. 3. 25 ft.
 WELL'S STATIC WATER LEVEL: 25 ft. below land surface measured on mo/day/yr 10-6-82
 Pump test data: Well water was NA ft. after NA hours pumping NA gpm
 Est. Yield 40 gpm Well water was NA ft. after NA hours pumping NA gpm
 Bore Hole Diameter: 9 in. to 13 ft., and 6 in. to 40 ft.
 WELL WATER TO BE USED AS:
 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well
 Was a chemical/bacteriological sample submitted to Department? Yes No
 Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded
 Blank casing diameter 5 in. to 32 ft., Dia. 12 in. to 1.59 lbs./ft. Wall thickness or gauge No. .209
 Casing height above land surface 12 in., weight 1.59 lbs./ft. Wall thickness or gauge No. .209
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)
 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 31 ft. to 40 ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From NONE ft. to ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 3 ft. to 13 ft., From ft. to ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? NORTH How many feet? 60

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	4	SANDY TOP SOIL BROWN			
4	16	SANDY CLAY RED			
16	32	SAND REDDISH FINE			
32	40	SAND COARSE TAN			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-6-82 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 104 This Water Well Record was completed on (mo/day/yr) 11/17/82 under the business name of BEARDEN PUMP & WELL by (signature) Os W Barden
 INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.