1 LOCATION OF WATER WELL:				FRACTION	V	- Wa	ier wen ket	and For	III W WC	Section Number	Township N	umber	Range N	umber
Sumner				NE	1/4	NE	1/4	SE	1/4	4	т 30		R 1E	
Distance		frem nearest town or ci	ty street								1 1 30	S	RIE	E/W
ı			•				•							
		le S. of					side	OI	Hyo	raulic				
	ATER WELL			LAND,	то	m					D			
RR#, ST. ADRESS, BOX#: R. R. # 1 CITY, STATE, ZIP CODE: Peck, Kansas Application Number:												ivivsion of water K	.esource	
	Y, STATE, ZII											Application Numbe	r:	
	TE WELL'S I	LOCATION WITH	_	DEPTH OI					30		LEVATION:			
, a	I I SECTIO	N N	D	epth(s) gro	oundw	ater Enc	ountered	1		ft.	2	ft.	3	ft.
			WEI	LL'S STAT	IC W	ATER L	EVEL .	16	FI	. BELOW LAND S	SURFACE MEASURED	ON mo/day/yr	08/09/	/1994
	NW.	NE.	l	Pun	np test	t data:	Wel	l water	was	ft.	after	hours pum	ping	gpm
۵.			Est.	Yield		gpm:	We	ll water	was	ft.	after	hours pum	ping	gpm
1 Mile	/ -	E	Bore	Hole Dian	neter	12	in.	to	30	ft.	and	in.	to	ft.
= '		X	WEL	L WATER	R TO I	BE USED	AS:	5 Pub	olic wate	er supply	8 Air conditioning	ng 11 I	njection well	
Ι.	sw		1	1 Domestic	:	3 Feed	lot	6 Oil	field w	ater supply	9 Dewatering	12 (Other (Specify	below)
H	"] 2	2 Irrigation	n	4 Indu	strial	7 Lav	vn and	garden only	10 Monitoring w	ell		
			Was	a chemical	l/bacte	riologica	l sample	submit	ted to D	epartment? Yes	No No	X ; If yes, m	o/day/yr samp	le was
		S	sub	mitted						N.	ater Well Disinfec	ted? Yes	X No	
5 TY	PE OF CA	SING USED:				5 Wro	ought iro	n		Concrete tile	CASING J	OINTS: G	lued X Clar	mped
1 Steel 3 RMP (SR)						6 Asbestos-Cement				Other (Specify	below)	Welded		
2 PV	С	4 ABS				7 Fibe	rglass		S	DR-26		Т	hreaded	
Blank c	asing Dian	eter 5	in.	to 24		ft	Dia		in.		ft., Dia	in.	to	ft.
ł	•	ve land surface			in.,	,	weight	2.3		lbs. / ft.	Wall thickness of			14
	-	EN OR PERFORA		MATERI			ugitv		_	7 PVC		Asbestos-cem		
1 Ste	el	3 Stainless Steel				5 Fiber	glass		:	RMP (SR)	1	l other (specify)	
2 Bra	188	4 Galvanized ste	el			6 Conc	rete tile			9 ABS	12	None used (or	en hole)	
SCREI	EN OR PE	RFORATION OP	ENING	G ARE:			5 Ga	auzed w	rapped		8 Saw cut		11 None (o	pen hole)
1 Continous slot 3 Mill slot							6 Wire wrapped				9 Drilled holes			
2 Louv	ered shutte	r 4 Key p	unche	d			7 To	rch cut	_		10 Other (sp	pecify)		
SCREE	N-PERFO	RATION INTERV	VALS:	fron	ո 24			ft. to 3	20	A F		•		ft.
	av I Diu O		• • • • • • • • • • • • • • • • • • • •						0	ft., Fro		ft. to		
					from ft. to ft. to 30			20	ft., From ft., From		ft. to		ft.	
GRAVEL PACK INTERVALS: from from						4 ft. to 30 ft. to			30	ft., From		ft. to ft. to		ft.
6 GR	OUT MAT	ERIAL: 1 Neat	cemer			ement g	rout	16. 60	3 R	ntonite	4 Other	14.10		16
	ntervals:			to 24									•	
		t source of possibl			,	IL.	From		π.	to 10 Lives	ft. Fron tock pens		ft. to	ft.
1 Septic tank 4 Lateral lines							11 Fuel	-	14 Abandon water well					
			.5	8 Sewage lagoon					ilizer storage	15 Oil well/Gas well 16 Other (specify below)				
2 Sewer lines 5 Cess pool 3 Watertight sewer lines 6 Seepage pit						9 Feedyard					cticide storage	None Apparent		
I	_	-	age pi	it		71	recuyaru				**		Appare	ent
Direction from well? FROM TO LITHOLOGIC LOC					LOG	FRO			FROM	ТО	How many i	DVAIS	· 	
0	3	topsoil	21111	OLOGIC	LOU			十	FROM	1 10	110	GGING INTE	KVALS	
3	16	clay								1	SEPTIC S	VSTEM N	ОТ	
16	23	fine sar	nd.								INSTALLE			₹
23	30	grey sha								1	INSTRULL	D MI III	10 1111	<u> </u>
2	130	Area suc	4TC						~					
			-											
-	1			· · · · · · · · · · · · · · · · · · ·										
					-									
		7												
	†					-								
	†													
	1	Ì					-							
	 							+						
7	.1								-	L				
CO	NTRACTO	R'S OR LANDOWNE	R'S CEI	RTIFICATIO	N: Thi	is water	well was	s (1) <u>co</u>	nstruc	ted, (2) recons	tructed, or (3) plu	igged under n	ny jurisdictio	n and
was c	ompleted	on (mo/day/year)	VX/.!		777¥.		and	this re	cord is true to	the best of my ki	nowledge and	belief. Kans	as Water
											mo/day/yr)	n¤.⁄.T	1.7.7.4	******
Under	the busin	ness name ofHi	arb.	¥2.7.7	₩	r.unp		X.J.C.S	к. /	M.C by (sig		0 9		
												Jane F	rederick	7