	WATER WELL RECORD For		32a-1212		
1 LOCATION OF WATER WELL:		Section Nun		1	- 1
County: Wilson	SW ¼ NW ¼ SW		т 30	s R 16	E
Distance and direction from nearest	town or city street address of well if located win 1003 Main Street, N		as		
2 WATER WELL OWNER: May	r's Apco, Neodesha c/o KDHE Tir				
RR#, St. Address, Box # : 100		una maten		ulture, Division of Water Resour	res
City, State, ZIP Code : Top			Application Nu		
LOCATE WELL'S LOCATON W	ITH .	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	Application No	inder.	
AN "X" IN SECTION BOX:	DEPTH OF COMPLETED WELL	16 ft.	ELEVATION:		
	Depth(s) Groundwater Encountered 1		ft. 2	ft. 3	Ft.
N	WELL'S STATIC WATER LEVEL 1	3.18 ft. below la	and surface measured of	on mo/day/yr 01/09/06	
A				hours pumping G	
	Est. Yield Gpm: Well water	was	Ft. after	Hours pumping G	ma
NW NE	Bore Hole Diameter 8.625 In. to	16	Ft. and	in. to	Ft.
W Mile	Bore Hole Diameter 8.625 In. to WELL WATER TO BE USED AS: 5 Pu 1 Domestic 3 Feed lot 6 Oil	iblic water supply	8 Air condition	ning 11 Injection well	
÷ ''	1 Domestic 3 Feed lot 6 Oil	I field water supply	9 Dewatering	12 Other (Specify belo)W)
X-swse	2 Irrigation 4 Industrial 7 La	wn and garden (don	nestic) 10 Monitoring	well MW-7	
i i	Was a chemical/bacteriological sample su	ubmitted to Departm	ent? Yes No X	if yes, mo/day/yr sample wa	as
†	Submitted			d? Yes No X	
5 TYPE OF BLANK CASING USE				ITS: Glued Clamped	
F	MP (SR) 6 Asbestos-Cement			Welded	
2 PVC 4 AE	•	o Other (specify	DOIOW)	Threaded X	
2 PVC 4 AE	r.				
Blank casing diameter 2	In. to 6 Dia	in. to	ft., Dia	in. to	ft.
Casing height above land surface	FLUSH in., weight SC	CH 40 Lt	s./ft. Wall thickness or	gauge No.	
TYPE OF SCREEN OR PERFORA		7 PVC	10 Asbe	stos-cement	
				r (specify)	
	alvanized steel 6 Concrete tile	9 ABS	12 None	e used (open hole)	
SCREEN OR PERFORATION OPE		d wrapped	8 Saw cut	11 None (open hole	:)
1 Continuous slot	3 Mill slot 6 Wire w	rapped	9 Drilled holes		
2 Louvered shutter	4 Key punched 7 Torch	cut	10 Other (speci	fy)	
SCREEN-PERFORATED INTERVA	ALS: From 6 ft. to	16	ft. From	ft. to	ft.
	From ft. to		ft. From	ft. to	Ft.
SAND PACK INTERVALS:	From 4 ft. to	16	ft. From	ft. to	Ft.
	From ft. to		ft. From	ft. to	Ft.
GROUT MATERIAL: 1 No	eat cement 2 Cement grout	3 Bentonite	4 Other		
	Ft.	Ft.			- 1
Grout Intervals From3 0	Ft. to 2 From2 2	to	4 ft. From	ft. to	ft.
What is the nearest source of possi			_ivestock pens	14 Abandoned water well	
1 Septic tank	4 Lateral lines 7 Pit privy	11 F	Fuel storage	15 Oil well/ Gas well	
2 Sewerlines	5 Cess pool 8 Sewage I	lagoon 12 F	ertilizer storage	16 Other (specify below)	
Watertight sewer lines	6 Seepage pit 9 Feedyard	13 1	nsecticide storage	Contaminated Site	•
Direction from well?		Hown	nany feet?		
FROM TO CODE	LITHOLOGIC LOG	FROM TO	PLU	IGGING INTERVALS	
	Asphalt and concrete				
	Clay (CL) brown to light gray				
16 TD	End of Borehole				
					-
		-			
					$\overline{}$
					$\neg \neg$
7 CONTRACTOR'S OR LANDOW	NER'S CERTIFICATION: This water well was	(x) constructed, (2)	reconstructed, or (3) pl	ugged under my jurisdiction and	w
Completed on (mo/day/yr)	01/04/06	And this record	d is true to the best of m	ny knowledge and belief. Kansa	s
Water Well Contractor's License No	585			ed on (mo/day/yr) 01/27/0	
under the business name of	Associated Environmenta	i, inc.	By (signature) Bra	adley J. Johnson	
INSTRUCTIONS:. Please fill in b	planks and circle the correct answers. Send three co	opies to Kansas Depa	rtment of Health and Envir	onment, Bureau of Water, Topeka,	
Kansas 66620-0001 Telephone	 913-296-5545. Send one to WATER WELL OWN 	JER and retain one for	vour records.		