


1 LOCATION OF WATER WELL: Fraction SE 1/4 NE 1/4 SE 1/4 Section Number 18 Township Number T 30 S Range Number R 16 **EW**  
 County: Wilson

Distance and direction from nearest town or city street address of well if located within city?  
Neodesha, Kansas

2 WATER WELL OWNER: Standard Oil Company Contact: Mr. Tony Gogal, (918)660-4007  
 RR#, St. Address, Box #: P.O. Box 591 Board of Agriculture, Division of Water Resources  
 City, State, ZIP Code: Tulsa, Oklahoma 74102 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  


4 DEPTH OF COMPLETED WELL: 30 ft. ELEVATION:  
 Depth(s) Groundwater Encountered 1. 30 ft. 2.        ft. 3.        ft.  
 WELL'S STATIC WATER LEVEL X        ft. below land surface measured on mo/day/yr 8/25/81  
 Pump test data: Well water was        ft. after        hours pumping        gpm  
 Est. Yield        gpm: Well water was        ft. after        hours pumping        gpm  
 Bore Hole Diameter: 8 in. to 30 ft., and        in. to        ft.  
 WELL WATER TO BE USED AS:  
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 11 Injection well  
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well 12 Other (Specify below)  
 Was a chemical/bacteriological sample submitted to Department? Yes        No X; If yes, mo/day/yr sample was submitted  
 Water Well Disinfected? Yes        No X

5 TYPE OF BLANK CASING USED:  
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued        Clamped         
2 PVC 4 ABS 7 Fiberglass        Welded         
 Blank casing diameter 2 in. to 30 ft., Dia.        in. to        ft., Dia.        in. to        ft.  
 Casing height above land surface 36 in., weight        lbs./ft. Wall thickness or gauge No.         
 TYPE OF SCREEN OR PERFORATION MATERIAL:  
 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement  
 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)         
 12 None used (open hole)  
 SCREEN OR PERFORATION OPENINGS ARE:  
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)  
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify)         
 7 Torch cut  
 SCREEN-PERFORATED INTERVALS: From 20 ft. to 30 ft., From        ft. to        ft.  
 From        ft. to        ft., From        ft. to        ft.  
 GRAVEL PACK INTERVALS: From 10 ft. to 30 ft., From        ft. to        ft.  
 From        ft. to        ft., From        ft. to        ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other         
 Grout Intervals From 0 ft. to 10 ft., From        ft. to        ft., From        ft. to        ft.  
 What is the nearest source of possible contamination:  
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well  
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well  
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)  
Refinery waste disposal pit  
 Direction from well? X How many feet?       

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	25	CLAY, brown with gravel			
25	30	CLAY, sandy, brown			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8/25/81 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No.        This Water Well Record was completed on (mo/day/yr) 11/10/81 under the business name of HEMPHILL CORPORATION by (signature) James R. Hemphill

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY T 30 R 16 EW SEC. R SE 1/4 NE 1/4 SE 1/4