


1 LOCATION OF WATER WELL: Fraction SW 1/4 NE SE 1/4 Section Number 18 Township Number T 30 S Range Number R 16 EW  
 County: Wilson

Distance and direction from nearest town or city street address of well if located within city?  
Neodesha, Kansas

2 WATER WELL OWNER: Standard Oil Company Contact: Mr. Tony Gogal  
 RR#, St. Address, Box #: P.O. Box 591  
 City, State, ZIP Code: Tulsa, Oklahoma 74102 (918)660-4007  
 Board of Agriculture, Division of Water Resources Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  
  
 4 DEPTH OF COMPLETED WELL: 25 ft. ELEVATION:  
 Depth(s) Groundwater Encountered 1. 25 ft. 2. 25 ft. 3. 25 ft.  
 WELL'S STATIC WATER LEVEL X 25 ft. below land surface measured on mo/day/yr 8/24/81  
 Pump test data: Well water was 25 ft. after 25 hours pumping 25 gpm  
 Est. Yield 25 gpm: Well water was 25 ft. after 25 hours pumping 25 gpm  
 Bore Hole Diameter 25 in. to 25 ft., and 25 in. to 25 ft.  
 WELL WATER TO BE USED AS:  
 5 Public water supply 8 Air conditioning 11 Injection well  
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)  
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well  
 Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted  
 Water Well Disinfected? Yes No X

5 TYPE OF BLANK CASING USED:  
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped  
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded  
 Blank casing diameter 2 in. to 25 ft., Dia. 25 in. to 25 ft., Dia. 25 in. to 25 ft.  
 Casing height above land surface 36 in., weight 36 lbs./ft. Wall thickness or gauge No. 36  
 TYPE OF SCREEN OR PERFORATION MATERIAL:  
 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement  
 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) 12 None used (open hole)  
 SCREEN OR PERFORATION OPENINGS ARE:  
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)  
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes  
 7 Torch cut 10 Other (specify) 12 None used (open hole)  
 SCREEN-PERFORATED INTERVALS: From 15 ft. to 25 ft., From 15 ft. to 25 ft., From 15 ft. to 25 ft.  
 GRAVEL PACK INTERVALS: From 10 ft. to 25 ft., From 10 ft. to 25 ft., From 10 ft. to 25 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other  
 Grout Intervals: From 0 ft. to 10 ft., From 10 ft. to 10 ft., From 10 ft. to 10 ft., From 10 ft. to 10 ft.  
 What is the nearest source of possible contamination:  
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well  
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well  
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)  
Refinery waste disposal pit  
 Direction from well? X How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	20	SILT, sandy, green, oily			
20	25	SANDSTONE, shaley, gray			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8/24/81 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 11/18/81 This Water Well Record was completed on (mo/day/yr) 11/18/81 under the business name of HEMPHILL CORPORATION by (signature) James R. Hemphill

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY T 30 R 16 EW SEC. 18 SW 1/4 NE 1/4 SE 1/4