properties to the second street and the second second	WATER WELL RE	CORD PO	orm vv vv		5A 82a-1212	<u> </u>		IMPER 1
1 LOCATION OF WATER WELL:	FRACTION	eie Ci c		ION NUMBER	1		RANGE NU	
Sumner	NE 1/4 NE		1/4	29	T 30	S	R 2E	E/W
Distance and direction from nearest town or city								
1049 N. Webb Road	Bell Plaine, K	ansas				·		
2 WATER WELL OWNER: VANDERWALL, Bill Board of Agriculture, Division of Water Resource								
	N. Webb Road					Doglo of Mgr	icaliare, Emoiorior vi	aici ricodarce
CITY, STATE: Bell	Plaine, Kansas			CODE:		Application Nur	mber:	<u> </u>
3 LOCATE WELL'S LOCATION 4	DEPTH OF COMPLETED W	/ELL: 39	ft,		ELEVATION:			
WITH AN "X" IN SECTION BOX: De	oth of groundwater Encounte	ered:	ft.			ft.		ft.
1 1	ELL'S STATIC WATER LEVI	EL 15	FT. BELO	W LAND SÚ	IRFACE MEASUR	RED ON mo/	day/yr: 6/19	/13
NWNE	Pump test da				ft, after		s of pumping @	gpm
	Est. Yield: gpm	Well water			ft, after		s of pumping @	gpm
W B	ore Hole Diameter 12		to 3	9 ft.		in.	to	ft.
	ELL WATER TO BE USED A					9. Dewater	44 1313	ction well
	. Domestic 3. Feedlot		er supply '	7. Lawn a	nd garden only	> Dewater	ing .	pecify below)
2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well								
s v	Vas a chemical/bacteriological sa			YES	NO	; If yes,	what mo/day/yr v	
su	bmitted		والمراثب المراكز المحجور والمرا	Was V	Vater Well Disinfe	cted?	YES I	10
5 TYPE OF CASING USED:	_ 5. Wrought Iron	7. Fiberglass	9. Ot	her (Specify	below) CASII	NG JOINTS:	Glued	Threaded
1. Steel 3. RPM (S	₹)		SDI	R-26	-		Welded	Clamped
2. PVC 4. ABS	6. Asbestos-Cement	8. Concrete tile	e SDI	. ₹ -20				
Blank casing diameter 5	in. to 29 ft.	, Dia.	in.	to	ft., D	ia.	in. to	ft.
Casing height above land surface:	12 in.,	Weight:	2.35 Ib	os. / ft.	Wall thic	kness or gau	ge No214	
TYPE OF SCREEN OR PERFORATION MATERIAL:								
1, Steel 3. Stainless Steel	5. Fiberglass C	7, PVC	9. A	BS	11. Oth	er (specify)		
2. Brass 4. Galvanized	6. Concrete Tile	8. RMP (SR)	10. A	sbestos-Cer	nent 12 Nor	e used (oper	n hole)	
						, ,		
SCREEN OR PERFORATION OPENINGS ARE:								
1. Continuous slot 3. Mill slot 5. Gauzed wrapped			نىنىنى	7. Torch cut 9. Drilled holes 11. None (open hole)				
2. Louvered shutter 4. Key p	unched 6. Wire wrap	pped	8. Sa	w cut	10. Othe	r (specify)		
SCREEN - PERFORATION INTERVAL	From 29	ft. to	39	ft.,	From	ft.	to	ft.
	From	ft, to		ft.,	From	ft.	to	ft.
CDAVE DACKINITEDVALC	2.4	ft. to	39					
GRAVEL PACK INTERVALS:	From 24			ft.,	From	ft,	to	ft.
	From	ft. to		ft.,	From	ft.	to	ft.
6 GROUT MATERIALS: 1. Neat	cement 2. Cen	nent Grout	3	B. Bentonite		Other ben	tonite hole pl	ug
Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft.								
What is the nearest source of possible contamination:					e e e	45 00	Sauranoir	
1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well								
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below)								
3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage								
Direction from well? Southwe					How ma	ny feet? 50	ft. plus	
From To	LITHOLOGIC LOG		From	То		LITHOL	OGIC LOG	
0 3 topsoil								
3 10 clay							· · · · · · · · · · · · · · · · · · ·	
10 15 fine sand		· · · · · · · · · · · · · · · · · · ·						
15 39 medium san	d							
				<u> </u>		<u> </u>		
<u></u>		 		 	<u> </u>		·	
				<u> </u>				
	and the second designation of the second des		ļ	 		·		
				 		···		
					<u> </u>			·
		<u></u>		 				
				 				
			 	+	** * * * *	<u> </u>		
		 	+	+	<u> </u>		·	
				 	 			4
7 Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and								
was completed on (mo/day/year)	6-19-2013	and this record i	is true to the	e best of my	knowledge and b	elief.		
Kansas Water Well Contractor's Lice	nse No. 236	This water we	ell record wa	as complete	d on (mo/day/yea	6-2	1-2013	
under the business name of Harp	well and Pump Ser	vice	by (s	ignature)	Ic	raa S	S. Hari).