| WATER WELL RECORD Form WWC-5 Divisi | on of Water Resources App. No. |
|--|---|
| 1 LOCATION OF WATER WELL: Fraction Section 1 | |
| County: Syroner 4 4 4 NE 4 6 | |
| Street/Rural Address of Well Location: if unknown, distance & direction Global P | ositioning System (GPS) information: |
| from nearest town or intersection: If at owner's address, check here . Latitude: | : (in decimal degrees) |
| Longitud | de: (in decimal degrees) |
| Elevation | n: |
| | ☐ WGS 84, ☐ NAD 83, ☐ NAD 27 |
| | n Method: |
| , | S unit (Make/Model:) |
| City, State, ZIP Code : Mulvane, KS 67117 | ital Map/Photo, ☐ Topographic Map, ☐ Land Survey rracy: ☐ <3 m, ☐ 3-5 m, ☐ 5-15 m, ☐ >15 m |
| | |
| 3 LOCATE WELL WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 65 | ft . |
| WITH AN "X" IN SECTION BOX: Depth(s) Groundwater Encountered (1).15 | |
| N WELL'S STATIC WATER LEVEL 15 | |
| Pump test data: Well water wasft. af | fter hours numning gpm |
| .]] | ter hours numping gnm |
| The state Dispersion 10 in to 65 ft and | in to fi |
| W E Bore Hole Diameter | Geothermal Thiection well |
| WELL WATER TO BE USED AS: Public water supply Geothermal Injection well Domestic Feedlot Oil field water supply Dewatering Other (Specify below) | |
| SW SE Domestic Feedlot Oil field water supply | en Monitoring well |
| ☐ Irrigation ☐ Industrial ☑ Domestic-lawn & garde | en [] Wonttoffing wen |
| Was a chemical/bacteriological sample submitted to Departme | ent! Lites Elivo |
| S If yes, mo/day/yr sample was submitted | |
| 1 mile Water well disinfected? | |
| 5 TYPE OF CASING USED: Steel PVC Other | |
| CASING IOINTS: 101 Glued Clamped Welded Threaded | |
| Casing diameter 5 in to 65 ft. Diameter in to | ft., Diameter in. to ft. |
| Casing height above land surface. 12 in., Weight 2.5 lbs./ft., Wall thickness or gauge No. SDR26 | |
| TYPE OF SCREEN OR PERFORATION MATERIAL: | |
| ☐ Steel ☐ Stainless Steel ☐ PVC ☐ Other (Specify) | |
| ☐ Brass ☐ Galvanized Steel ☐ None used (open hole) | |
| SCREEN OR PERFORATION OPENINGS ARE: | passed = |
| | d holes |
| Louvered shutter Key punched Wire wrapped Saw cut Other | (specify) |
| SCREEN-PERFORATED INTERVALS: From 25 ft. to 65 ft. to 65 | T., From It. W It. |
| GRAVEL PACK INTERVALS: From 20 ft. to 65 ft. | ft., From |
| GRAVEL PACK INTERVALS: From | ft., From ft. to ft. |
| From | Other |
| 6 GROUT MATERIAL: Neat cement Cement grout Bentonite Corout Intervals: From 3 ft. to .20 ft., From ft. to | ft From ft to ft |
| Grout Intervals: From | 10., 110111 |
| What is the nearest source of possible contamination: ☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ | Insecticide storage |
| | Abandoned water well |
| | Oil well/gas well |
| | . 20' |
| | LITHO. LOG (cont.) or PLUGGING INTERVALS |
| 0 3 Topsoil | |
| 3 10 Clay - | |
| | |
| | |
| 15 65 Shale | |
| | |
| | |
| | |
| | |
| | |
| | prog |
| 7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was | s constructed, reconstructed, or plugged |
| under my jurisdiction and was completed on (mo/day/year) .05/01/2015 and this record is true to the best of my knowledge and belief. | |
| Kansas Water Well Contractor's License No. 238. This Water Well Record was completed on (mo/day/year) 5/04/2015. under the business name ofPremier Pump & Well Service, Inc. by (signature) | |
| under the business name of Premier Pump & Well Service, Inc. by (signature) W. | |
| I INCTED IT THANK: The typewriter of ball boint ben PLEANE PRESS FIRMLY 2010 PRINT CICATIV. FICASC | illi ili bialiks alid check the correct this wers. Sond one copy to |
| Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at | |
| http://www.kdheks.gov/waterwell/index.html | |