1 LOCATION OF WATER WELL:		FRACTION		-			Section Number	Township Number	Range Number	
Sumner		SE 1/4	NE	1/4	SE	1/4	32	т 30 s	R 2E EW	
Distance and direction	frem nearest town or city stre	eet address of well if lo	cated within city	y?						
3 m. E.	of Belle	Plaine,	3/8 m.	N.	of	Hwy	155, NW	side Belle Pi	laine, Ks.	
2 WATER WELL						_				
RR#, ST. ADRESS,	2727 11 12	Box 24						Board of Agriculture, I	Divivsion of Water Resource	
CITY, STATE, ZIF		Plaine,						Application Numb	er:	
3 LOCATE WELL'S I	N DOV.	DEPTH OF CO				50		VATION:		
t [N	Depth(s) ground					ft.	2 ft.	3 ft.	
		ELL'S STATIC V Pump te			_			RFACE MEASURED ON mo/day/yr	10/13/1992	
NW	NE NE	. Yield			ll water ll water			after hours pur		
		. 1 ieiu re Hole Diameter	gpm: 12	in.		was 50	ft. ft. ,	after hours pun and in.	nping gpm to ft.	
1Mile M	1.5	ELL WATER TO							Injection well	
1		1 Domestic	3 Feedlo					-	Other (Specify below)	
sw	sie7-3	2 Irrigation	4 Indust	rial				0 Monitoring well		
	Wa	as a chemical/bac	teriological :	sample	submitte	ed to D	epartment? Yes	No X ; If yes, 1	no/day/yr sample was	
	C .	ıbmitted					-	ter Well Disinfected? Yes	X No	
5 TYPE OF CA	SING USED:		5 Wrou	ght iro	n		8 Concrete tile	CASING JOINTS:	Glued X Clamped	
1 Steel					Other (Specify be		Welded			
2 PVC	4 ABS		7 Fiberg	glass		S	DR-26		Threaded	
Blank casing Dian	eter 5 in.	to 30	ft.,	Dia		in	. to	ft., Dia in.	to ft.	
	ve land surface 12	in.	, ,	weight	2.	35		Wall thickness or gauge No.	.214	
	EN OR PERFORATIO	ON MATERIAL:	5 Fibergl	oce			7 <u>PVC</u> 8 RMP (SR)	10 Asbestos-cen		
1 Steel	3 Stainless Steel		6 Concre					11 other (specif	• /	
2 Brass	4 Galvanized steel		o Concre				9 ABS	12 None used (c 8 Saw cut	• ′	
1 Continous slot	RFORATION OPENIN	NG ARE:			auzed wr	• •		9 Drilled holes	11 None (open hole)	
2 Louvered shutte	3 Mill slot r 4 Key punch	had			ire wrap	peu		10 Other (specify)		
	RATION INTERVAL	_	_		rch cut				Δ.	
SCREEN-FERFO	RATION INTERVAL	J	U		ft. to 5	U	ft., From			
CPAV	EL PACK INTERVAL	from LS: from 2	A		ft. to	50	ft., Fron ft., Fron		ft.	
GICAV	ELTACK INTERVAL	from 2	*		ft. to	50	ft., Fron			
6 GROUT MAT	ERIAL: 1 Neat cem		Cement gro	ut		3 Be	entonite	4 Other		
Grout Intervals:	From 4 ft	t. to 24	ft., F	rom		ft.	to	ft., From	ft. to ft.	
What is the nearest source of possible contamination:							10 Livesto	•	Abandon water well	
1 Septic tank 4 Lateral lines				7 Pit privy			11 Fuel st	13	15 Oil well/Gas well	
2 Sewer lines 5 Cess pool				8 Sewage lagoon				aldo etemano	16 Other (specify below)	
3 Watertight sew		pit	9 Fe	eedyard	d		15 Hisecu	Non	e Apparent	
Direction form we		HOLOGICI O	7			20014		How many feet?	CDS/AT C	
FROM TO 3	topsoil	HOLOGIC LOC	3			FROM	ТО	PLUGGING INT	ERVALS	
3 16	fine sand				_					
16 32	medium san	nd.								
32 50	medium to		sand							
7 CONTRACTO	T				- (1)		4-1.00			
CONTRACT	OR'S OR LANDOWNER'S (CERTIFICATION: T	his water w /1992	vell wa	s (1) <u>co</u>	nstruc	ted, (2) reconstr	ucted, or (3) plugged under ne best of my knowledge an	my jurisdiction and	
Well Contracto	r's License No. 2	236	mar.ar.ar . This Wat	er Wel	and Record	d was	completed on /m	no/day/yr)11./1	LO/92	
	ness name ofHar							ature	rederick	
							minimum wy torsain	11/2/2		