1 LOCATION OF WATER WELL:		FRACTION	Water Wel	ll Record F	Form WWC	-5 KSA 82a-121 Section Numi		nber	Range Number	
Sumner		SW 1/4	SE 1/4	4 NE	1/4	21	т 30	s	R 2E E/W	
Distance and direction frem nearest town or city street address of well if located within city?										
1 1/2 m.	. E. of Mu	lvane, 3	1/2 m.	s.,	1/4	m. Wes	t Mulva	ane, Ka	nsas	
2 WATER WELL OW		DSON, Ker								
RR#, ST. ADRESS, BOX#: Rt 1 Box 577A							Board of Agriculture, Divivsion of Water Resource			
CITY, STATE, ZIP CO	ODE: Mulya	ne, Kansa	as			67110	A	pplication Number	r:	
3 LOCATE WELL'S LOC AN "X" IN SECTION E	POV.	DEPTH OF CO			50	ft.	ELEVATION:			
AN "A" IN SECTION E	N .	Depth(s) groundw			1	ft.	2	ft.	3 ft.	
	W	ELL'S STATIC W		_		T. BELOW LAN	D SURFACE MEASURED	• •	07/27/1994	
NW	NE.	Pump tes		Well water		ft	. after	hours pum		
<u> </u>	N 1 1	t. Yield	- T	Well water		f		hours pum		
💆 w	~	re Hole Diameter		in. to		ft.		in.	to ft.	
"		ELL WATER TO				ter supply	8 Air conditionin	-	njection well	
sw	sæ	1 Domestic	3 Feedlot 4 Industrial			vater supply garden only	9 Dewatering		Other (Specify below)	
		2 Irrigation		_			10 Monitoring wel		- /-law/swample was	
	C	as a chemical/bact ubmitted	eriologicai sam	aple subm	itted to 1	Department?	Yes No Water Well Disinfect		no/day/yr sample was **No	
5 TYPE OF CASI	su	1Dmitteu	- Wanah	4 •		S.Cmamata til			X No	
1 Steel	3 RMP (SR)		5 Wrought iron 6 Asbestos-Cement			8 Concrete tile CASING JOINTS: Glued X Clamped 9 Other (Specify below) Welded				
2 PVC	4 ABS		7 Fiberglas			SDR-26	ny below,		Threaded	
Blank casing Diamet		. to 27	_	Dia	-	n. to	ft., Dia	in.	to ft.	
Casing height above	•	. 10 2 / in.,		иа ight 2. 3		n. to lbs./ft.	Wall thickness or		.214	
	OR PERFORATIO		•		, ,	7 PVC		Asbestos-ceme		
1 Steel 3	3 Stainless Steel		5 Fiberglass	ŝ		8 RMP (SR)	` 11	other (specify	7)	
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)										
SCREEN OR PERF	FORATION OPENI	NG ARE:		5 Gauzed	wrapped	1	8 Saw cut		11 None (open hole)	
1 Continous slot	3 Mill slot		(6 Wire wr	apped		9 Drilled hole	s		
2 Louvered shutter	4 Key punch	hed	7	7 Torch cu	ıt		10 Other (sp	ecify)		
SCREEN-PERFOR	ATION INTERVAL	LS: from 27	7	ft. to	50	ft.,	From	ft. to	ft.	
		from	,	ft. to	,			ft. to	ft.	
GRAVEI	L PACK INTERVAL	LS: from 24				,	From	ft. to	ft.	
		ft. to			From	ft. to	ft.			
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other										
Grout Intervals: Fr		ft. to 24	ft. Fron	m	ft	t. to	ft. From		ft. to ft.	
What is the nearest s	_					10 Livestock pens		14 Abandon water well		
1	4 Lateral li	nes	7 Pit p			11 Fuel storage		15 Oil well/Gas well		
2 Sewer lines	5 Cess poo		-	ige lagoon		12 Fertilizer storage 13 Insecticide storage		16 Other (specify below)		
3 Watertight sewer		pit	9 Feed	yard		13 11	isecticide storage	None	Apparent	
Direction from well?					22.01		How many fo			
FROM TO 3		THOLOGIC LOG			FROM	1 TO	PLU	GGING INTE	RVALS	
	topsoil clay									
	medium sar	~~3								
	grey clay		<u> </u>							
	fine sand									
	grey shale									
	3									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and										
was completed on (mo/day/year)										
Well Contractor's License No236										
Under the business name of										
Jane Frederick										