WATER WELL RECORD	Form WWC-5	Division of Water	Resources App. No	0.	
1 LOCATION OF WATER WELL:	Fraction	Section Number			
County: Crawford	1/4 NW1/4 NE 1/4 NE	¼ 33		R JS ME □W	
Street/Rural Address of Well Location	n; if unknown, distance & direction		System (GPS) in	formation:	
from nearest town or intersection: If a	nt owner's address, check here	Latitude:	***************************************	(in decimal degrees)	
110 Bobwhite Lane, Pittsburg KS		Elevation:	Longitude: (in decimal degrees) Elevation:		
2 WATER WELL OWNER: October 10 - 10 - 10 - 10 - 10 - 10 - 10 - 10		- J <u>Datum</u> : ☐ WGS 84,	, 🔲 NAD 83, 🔲	NAD 27	
RR#, Street Address, Box #: City State ZIP Code		Collection Method:	Madel.	,	
			☐ GPS unit (Make/Model:) ☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey		
Fron	tenac KS 66763	Est. Accuracy: <			
2 LOCATE WELL	D1				
WITH AN "X" IN 4 DEPTH O	F COMPLETED WELL	メ.O.C	6-200'	bores	
	indwater Encountered (1)N				
	WELL'S STATIC WATER LEVEL Name ft. below land surface measured on mo/day/yr				
Pun	Pump test data: Well water wasft. after				
ESI. YIELD	EST. YIELD No. e. gpm. Well water was				
W E Bore Hole Dia	Bore Hole Diameter				
SWSE Domestic Feedlot Oil field water supply Dewatering Other (Specify below) Irrigation Industrial Domestic-lawn & garden Monitoring well C. 105 c					
Was a chemical/bacteriological sample submitted to Department? Yes No					
S If yes, mo/day/yr sample was submitted					
Water well disinfected? Yes No					
5 TYPE OF CASING USED: Steel PVC & Other H.D. Polyethylene					
CASING JOINTS: Glued Clamped Welded Threaded Fusion					
Casing diameter 314 in to 200 ft., Diameter in to ft., Diameter in to ft., Diameter in to ft. Casing height 200 land surface in, Weight 50.81/lbs./ft., Wall thickness or gauge No. 160.75.1					
TYPE OF SCREEN OR PERFORATION MATERIAL: No.					
Steel Stainless Steel PVC Other (Specify)					
☐ Brass ☐ Galvanized Steel ☐ None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE: None					
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)					
Louvered shutter					
SCREEN-PERFORATED INTERVALS					
From					
From ft to ft From ft to ft					
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other					
Grout Intervals: From 300 ft. to 3 ft., From ft. to ft., From ft. to ft., From ft. to ft.					
What is the nearest source of possible contamination:					
Septic tank Lateral lines Pit privy Livestock pens Insecticide storage Other (specify below)					
Sewer lines					
☐ Watertight sewer lines ☐ Seepag	. — . —	2		•••••	
Direction from well	OGIC LOG FROM	ce from well		ICCINIC INTERVALS	
			G (com.) or PLO	IGGING INTERVALS	
9 / So.1+clay)	116-132 Shale 191 32-148 Sand	200 Sand	·		
18 33 Shale 1	48-158 Shalf				
18 32 Shale 11 32 41 lime 11	58-162 lime				
41 63 Shale	62-168 Sand 200	3 6-200' F	sores plus	and wallh	
63 78 Sand 16	8-170 ling	1 20 1 6	Solid By	ged with	
78 95 Shale /17	0-174 Sand	+ ngn	JULIA GE	A FOALTE	
95 97 Sand 11	4-178 line				
97 111 51 10	8-183 Shale				
11 116 line 18	3-191 line			-	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ★ constructed, □ reconstructed, or ★ plugged					
under my jurisdiction and was completed on (mo/day/year) \$3.41 and this record is true to the best of my knowledge and belief.					
Kansas Water Well Contractor's License No. 5.6.1 This Water Well Record was completed on (mo/day/year) 3					
under the business name of E. V. ans. Energy Dev. Inc. by (signature)					
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASH PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send three copies					
(white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at					
http://www.kdheks.gov/waterwell/index.html.					
KSA 82a-1212					