

WATER WELL RECORD

Form WWC-5

Division of Water Resources; App. No.

1 LOCATION OF WATER WELL: County: Cowley Fraction: SE 1/4 NW 1/4 NE 1/4 Section Number: 26 Township Number: T 30 S Range Number: R 3 E Distance and direction from nearest town or city street address of well if located within city? 3 Mile West of Rock Ks, Global Positioning Systems (decimal degrees, min. of 4 digits) Latitude: Longitude: Elevation: Datum: Data Collection Method:

2 WATER WELL OWNER: Denness McCart RR#: 1618 S Sharon Cr. City, State, ZIP Code: Wichita Kan 67037

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing a 3x3 grid with 'X' in the NE section] 4 DEPTH OF COMPLETED WELL: 190 ft. Depth(s) Groundwater Encountered: (1) 190 ft. WELL'S STATIC WATER LEVEL: 50 ft. below land surface measured on mo/day/yr. Pump test data: Well water was 50 ft. after 50 gpm. Est. Yield: 50 gpm. WELL WATER TO BE USED AS: 1 Domestic, 2 Irrigation, 3 Feedlot, 4 Industrial, 5 Public water supply, 6 Oil field water supply, 7 Domestic (lawn & garden), 8 Air conditioning, 9 Dewatering, 10 Monitoring well, 11 Injection well, 12 Other (Specify below). Was a chemical/bacteriological sample submitted to Department? No. Water well disinfected? Yes.

5 TYPE OF CASING USED: 1 Steel, 2 PVC, 3 RMP (SR), 4 ABS, 5 Wrought Iron, 6 Asbestos-Cement, 7 Fiberglass, 8 Concrete tile, 9 Other (specify below), 10 Asbestos-Cement. CASING JOINTS: Glued, Clamped, Welded, Threaded. Blank casing diameter: 50 in. to 50 ft., Diameter. Casing height above land surface: 18 in., Weight: 160 lbs./ft., Wall thickness or gauge No. 1214. TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel, 2 Brass, 3 Stainless Steel, 4 Galvanized Steel, 5 Fiberglass, 6 Concrete tile, 7 PVC, 8 RM (SR), 9 ABS, 10 Asbestos-Cement, 11 Other (Specify), 12 None used (open hole). SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot, 2 Louvered shutter, 3 Mill slot, 4 Key punched, 5 Gauzed wrapped, 6 Wire wrapped, 7 Torch cut, 8 Saw Cut, 9 Drilled holes, 10 Other (specify), 11 None (open hole). SCREEN-PERFORATED INTERVALS: From 50 ft. to 190 ft. GRAVEL PACK INTERVALS: From 50 ft. to 190 ft.

6 GROUT MATERIAL: 1 Neat cement, 2 Cement grout, 3 Bentonite, 4 Other. Grout Intervals: From 3 ft. to 23 ft. What is the nearest source of possible contamination: 1 Septic tank, 2 Sewer lines, 3 Watertight sewer lines, 4 Lateral lines, 5 Cess pool, 6 Sewage lagoon, 7 Pit privy, 8 Sewage lagoon, 9 Feedyard, 10 Livestock pens, 11 Fuel storage, 12 Fertilizer Storage, 13 Insecticide Storage, 14 Abandoned water well below, 15 Oil well/gas well, 16 Other (specify below). Direction from well? N How many feet? 200

Table with columns: FROM, TO, LITHOLOGIC LOG, FROM, TO, PLUGGING INTERVALS. Rows: 0-4 Soil, 4-10 Rock, 10-18 Clay, 18-190 Shale + Lime

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo/day/year) 6/14/06 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 251. This Water Well Record was completed on (mo/day/year) 6/29/06 under the business name of Winter Well Drilling by (signature) Charles Winters

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well. Visit us at http://www.kdhe.state.ks.us/geo/waterwells.