			WATE	R WELL RECORD	Form W	WC-5 KSA 82a	-1212		
1 LOCATION		R WELL:	Fraction			Section Number		Range Number	
County: COW		rom poarcet to	NE 1/4				T 30S S	R 3E E/W	
1			side (from 1		aleu within t	orty :			
2 WATER W			l Howard		NW NW NW NW NW NW NW NW				
RR#, St. Addr			2, Box 46				Board of Agriculture	, Division of Water Resources	
City, State, ZII									
J LOCATE W	ELL'S LO	CATION WITH							
	N	DOX.							
Ī	•								
	√w -	- NE							
	!	!	1						
* w	1	i E	I	O BE USED AS:					
-	1	!	Domestic	3 Feedlot	6 Oil fiel	d water supply	9 Dewatering 12	2 Other (Specify below)	
	sw -	SE	2 Irrigation	4 Industrial	7 Lawn	and garden only	10 Monitoring well		
	<u> </u>	1		pacteriological samp	ole submitted				
EL TYPE OF F	S ANK 64	CINC LICED.	mitted	E Missisht ison	0.0				
5 TYPE OF E	SLANK CA	ASING USED:	B)	_				· I	
2)PVC			• •/	7 Fiberglass		` ' '	•		
Blank casing of			.in. to60						
_		_							
TYPE OF SCE	REEN OR	PERFORAT!O	N MATERIAL:			PVC	10 Asbestos-cer	nent	
1 Steel									
2 Brass	DEDEOD.								
			ted steel 6 Concrete tile 9 ABS 12 None used (open hole) IGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) Iill slot 6 Wire wrapped 9 Drilled holes ey punched 7 Torch cut 10 Other (specify) From 60 ft. to ft. From ft. to From ft. to ft. From ft. to ft.						
SCREEN-PERFORATED INTERVALS: From 6.0 ft. to 80 ft., From ft. to ft.									
GRA	VEL PAC	K INTERVALS:							
al apout w	ATEDIAL	4 N1							
6 GROUT MA				•					
1 Septic	tank	4 Later	ral lines	7 Pit privy			•		
2 Sewer lines 5 Cess poo			s pool	8 Sewage lagoon		12 Fertili	zer storage 16	Other (specify below)	
3 Watert	tight sewe	r lines 6 Seep	page pit	9 Feedyard	j	13 Insec	ticide storage		
Direction from			LITHOLOGIC	100	T EBC			INTERVALE	
FROM 0		Class		LUG	FAC	10	LOGGING	INTERIVALS	
1 1									
1 1		Lime W/							
1 1	1		some sand						
1 1		Lime							
80 !	90	Shale							
								467	
	L								
	Threaded. In gliameter 5 in to 60 ft. Dia 5 in to 80-90 .ft. Dia in to ft. pglit above land surface 24 in, weight by .ft. Wall thickness or gauge No. SDR 26 SCREEN OR PERFORATION MATERIAL. SCREEN OR PERFORATION MATERIAL. SCREEN OR PERFORATION MATERIAL. SI Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) ass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) State of the state								
(Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) N-PERFORATED INTERVALS: From 60 ft. to 80 ft. From ft. to ft. From ft. to 80 ft. From ft. to ft. From ft. to 90 ft. From ft. to ft. UIT MATERIAL: 1 Neat cement Ocement grout 3 Bentonite 4 Other Nervals: From 4 ft. to 20 ft. From ft. to ft. Hervals: From 4 ft. to 20 ft. From ft. to ft. Hervals: From 4 ft. to 20 ft. From ft. to ft. Hervals: From 6 ft. to ft. Hervals: From 6 ft. to ft. Hervals: From 7 ft. to ft. Hervals: From 6 ft. to ft. Hervals: From 7 ft. to ft. Hervals: From 6 ft. to ft. Hervals: From 7 ft. to ft. Hervals: From 6 ft								
INSTRUCTIO	NS: Use type	writer or ball point	pen. PLEASE PRESS F	IRMLY and PRINT clearly	. Please fill in b	anks, underline or circle	the correct answers. Send top three	e copies to Kansas Department	
of Health and	d Environmer	nt, Bureau of Water,	, Topeka, Kansas 6662	0-0001. Telephone: 913-2	96-5545. Send	one to WATER WELL OV	NNER and retail one for your recor	ds.	