

Form WWC-5 KSA 82a-1212 MS 7- MWSB04

1 LOCATION OF WATER WELL: Fraction NW 1/4 SE 1/4 SW 1/4 Section Number 28 Township Number T 30S S Range Number R 4E EW

Distance and direction from nearest town or city street address, or point located within city? 3 MILES SOUTHWEST OF BURLINGTON ON HIGHWAY 77 MW4

2 WATER WELL OWNER: McCONNELL AFB 90 TETRA TECH, INC

RR#, St. Address, Box #: 10 E. CAMBRIDGE CIRCLE DR STE 130 Board of Agriculture, Division of Water Resources

City, State, ZIP Code: KANSAS CITY, KS 66103 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL: 88.0 ft. ELEVATION: 82.0 ft.

Depth(s) Groundwater Encountered 1. 82.0 ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL 82 ft. below land surface measured on mo/day/yr

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter 8.75 in. to 88.0 ft. and in. to ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped

2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded

Blank casing diameter 4 in. to 68.0 ft. Dia. in. to ft. Dia. in. to ft.

Casing height above land surface in., weight lbs./ft. Wall thickness or gauge No. Sch 40

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement

2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)

12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)

2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify)

7 Torch cut

SCREEN-PERFORATED INTERVALS: From 68.0 ft. to 78.0 ft. From ft. to ft.

GRAVEL PACK INTERVALS: From 66.0 ft. to 78.0 ft. From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other 3/8" HOLE PLUG

Grout Intervals: From 0.0 ft. to 64.0 ft. From 64.0 ft. to 66.0 ft. From 66.0 ft. to 78.0 ft. From 78.0 ft. to 88.0 ft.

What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well

2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well

3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)

13 Insecticide storage

Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0.0	7.0	BROWN CLAY - MOIST FILL MATERIAL			
7.0	15.0	TAN LIMESTONE - WEATHERED, HARD			
15.0	38.0	TAN SHALEY LIMESTONE - MOIST			
38.0	88.0	GRAY SHALEY LIMESTONE - DRY, HARD			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-17-95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 551 This Water Well Record was completed on (mo/day/yr) 11-1-95 under the business name of ASSOCIATED ENVIRONMENTAL INDUSTRIES (signature)

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4