

1 LOCATION OF WATER WELL	Fraction	Section Number	Township Number	Range Number
County: <u>SUMNER</u>	<u>SE 1/4 SE 1/4 SE 1/4</u>	<u>13</u>	<u>T 31 S</u>	<u>R 1 E EW</u>

Distance and direction from nearest town or city? 3 S., 1 E., of Belle Plaine, Ks., Belle Plaine, Ks.
 Street address of well if located within city?

2 WATER WELL OWNER: Mr. Troutman
 RR#, St. Address, Box #: R.1
 City, State, ZIP Code: Belle Plaine, Ks.
 Board of Agriculture, Division of Water Resources
 Application Number:


3 DEPTH OF COMPLETED WELL: 50 ft. Bore Hole Diameter: 11 in. to ... ft., and ... in. to ... ft.
 Well Water to be used as:
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well
 Well's static water level: 1.4 ft. below land surface measured on 9 month 17 day 80 year
 Pump Test Data: Well water was ... ft. after ... hours pumping ... gpm
 Est. Yield: gpm: Well water was ... ft. after ... hours pumping ... gpm

4 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile Casing Joints: X Glued X Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded
 Blank casing dia: 5 in. to 3.5 ft., Dia ... in. to ... ft., Dia ... in. to ... ft.
 Casing height above land surface: 1.2 in., weight ... lbs./ft. Wall thickness or gauge No. 200
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
 Screen or Perforation Openings Are:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut .06 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify)
 Screen-Perforation Dia: 5 in. to 50 ft., Dia ... in. to ... ft., Dia ... in. to ... ft.
 Screen-Perforated Intervals: From 35 ft. to 50 ft., From ... ft. to ... ft.
 Gravel Pack Intervals: From 14 ft. to 50 ft., From ... ft. to ... ft.

5 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grouted Intervals: From 4.0" ft. to 1.4 ft., From ... ft. to ... ft.
 What is the nearest source of possible contamination:
1 Septic tank 4 Cess pool 7 Sewage lagoon 11 Fertilizer storage 14 Abandoned water well
2 Sewer lines 5 Seepage pit 8 Feed yard 12 Insecticide storage 15 Oil well/Gas well
3 Lateral lines 6 Pit privy 9 Livestock pens 13 Watertight sewer lines 16 Other (specify below)
 Direction from well: Northwest How many feet: 58? Water Well Disinfected? Yes X No
 Was a chemical/bacteriological sample submitted to Department? Yes ... No X If yes, date sample was submitted ... month ... day ... year: Pump Installed? Yes ... No X
 If Yes: Pump Manufacturer's name ... Model No. ... HP ... Volts
 Depth of Pump Intake ... ft. Pumps Capacity rated at ... gal./min.
 Type of pump: 1 Submersible 2 Turbine 3 Jet 4 Centrifugal 5 Reciprocating 6 Other

6 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on 9 month 17 day 80 year and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236
 This Water Well Record was completed on 10 month 31 day 1980 year under the business name of Harp Well & Pump Service, Inc. by (signature) M. Arnold

7 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
		0	3	Topsoil		
	3	16	Clay			
	16	38	Fine Sand			
	38	50	Grey Shale			



ELEVATION:
 Depth(s) Groundwater Encountered 1.14 ft. 2. ... ft. 3. ... ft. 4. ... ft. (Use a second sheet if needed)

INSTRUCTIONS: Use typewriter or ball point pen, please press firmly and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Water Well Contractors, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY
T
R
SEC.
13
SE 1/4 SE 1/4 SE 1/4