


1 LOCATION OF WATER WELL: County: SUMNER Fraction: SW 1/4 NE 1/4 NW 1/4 Section Number: 26 Township Number: T 31 S Range Number: R 1 EW

Distance and direction from nearest town or city street address of well if located within city?
4 MILLS SOUTH 6 TENTHS WEST - BELL PLAIN KANSAS

2 WATER WELL OWNER: H.C. PALSTON
 RR#, St. Address, Box #: 619 N. SUMNER Board of Agriculture, Division of Water Resources
 City, State, ZIP Code: BELL PLAIN KANSAS 67013 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:


4 DEPTH OF COMPLETED WELL: 23 ft. ELEVATION:
 Depth(s) Groundwater Encountered 1. 10 ft. 2. 2 ft. 3. 10 ft.
 WELL'S STATIC WATER LEVEL: 0 ft. below land surface measured on mo/day/yr 4-26-87
 Pump test data: Well water was 12 ft. after 2 hours pumping 10 gpm
 Est. Yield 10 gpm: Well water was 10 ft. after 10 hours pumping 10 gpm
 Bore Hole Diameter: 10 in. to 23 ft., and 10 in. to 10 ft.
 WELL WATER TO BE USED AS:
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well
 Was a chemical/bacteriological sample submitted to Department? Yes ✓ No ✓; If yes, mo/day/yr sample was submitted

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued ✓ Clamped ✓
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded ✓
 7 Fiberglass Threaded ✓
 Blank casing diameter 5 in. to 11 ft., Dia 11 in. to 11 ft., Dia 11 in. to 11 ft.
 Casing height above land surface: 30 in., weight 2.37 lbs./ft. Wall thickness or gauge No. 250
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 11 Other (specify)
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 12 ft. to 23 ft., From 12 ft. to 23 ft., From 12 ft. to 23 ft., From 12 ft. to 23 ft.
 GRAVEL PACK INTERVALS: From 10 ft. to 23 ft., From 10 ft. to 23 ft., From 10 ft. to 23 ft., From 10 ft. to 23 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other 0-3' SURFACE SOIL
 Grout intervals: From 3 ft. to 10 ft., From 10 ft. to 10 ft., From 10 ft. to 10 ft., From 10 ft. to 10 ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
FARM POND
 Direction from well? WEST How many feet? 150

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	4	DARK HEAVY SURFACE SOIL			
4	10	DIRT-STREAKS OF CLAY			
10	18	COURSE SAND			
18	20	SHALE, GRAY			
20	23	GRAY CLAY			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-26-87 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 437 This Water Well Record was completed on (mo/day/yr) 4-28-87 under the business name of RALPH THE TOWER WELL DIGGING SERVICE

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Office of Oil Field and Environmental Geology, Regulation and Permitting Section, Topeka, Kansas 66620-7500, Telephone: 913-862-9360. Send one to WATER WELL OWNER and retain one for your records.