

1 LOCATION OF WATER WELL: Sumner	FRACTION 1/4 C of NE 1/4	Section Number 20	Township Number T 31 S	Range Number R 2E E/W
--	------------------------------------	-----------------------------	----------------------------------	---------------------------------

Distance and direction from nearest town or city street address of well if located within city?

2 m. E., 3 m. S., 3/4 m. E., 1/4 m. S. of Belle Plaine, Kansas

WATER WELL OWNER: HISKEN, Doug	Board of Agriculture, Division of Water Resource
RR#, ST. ADDRESS, BOX #: 1459 E. 60th North	Application Number: 41.894
CITY, STATE, ZIP CODE: Belle Plaine, Kansas	

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL 57 ft. ELEVATION:
	Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft.
	WELL'S STATIC WATER LEVEL 13 FT. BELOW LAND SURFACE MEASURED ON 07/08/1996
	Pump test data: Well water was ft. after hours pumping gpm Est. Yield 700 gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 30 in. to 57 ft. and in. to ft.
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well	
Was a chemical/bacteriological sample submitted to Department? Yes ☐ No ☒ If yes, mo/day/yr sample was submitted	
Water Well Disinfected? Yes ☒ No ☐	

5 TYPE OF CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS:
1 Steel	6 Asbestos-Cement	9 Other (Specify below)	Glued ☒ Clamped
2 PVC	7 Fiberglass	SDR-26	Welded
Blank casing Diameter 16 in. to 27 ft., Dia			Threaded
Casing height above land surface 12 in., weight 19.750 lbs. / ft.			Wall thickness or gauge No. .616
TYPE OF SCREEN OR PERFORATION MATERIAL:	5 Fiberglass	8 RMP (SR)	11 other (specify)
1 Steel	6 Concrete tile	9 ABS	12 None used (open hole)
2 Brass			
SCREEN OR PERFORATION OPENING ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	6 Wire wrapped	9 Drilled holes	
2 Louvered shutter	7 Torch cut	10 Other (specify)	
SCREEN-PERFORATION INTERVALS:	from 27 ft. to 57 ft., From	ft. to	ft.
	from	ft. to	ft.
GRAVEL PACK INTERVALS:	from 20 ft. to 57 ft., From	ft. to	ft.
	from	ft. to	ft.

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other bentonite hole plug
Grout Intervals: From 0 ft. to 20 ft. From		ft. to	ft. From	ft. to
What is the nearest source of possible contamination:				
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandon water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	None Apparent

Direction from well?

How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	soil			
2	13	brown clay			
13	25	fine to coarse sand			
25	45	fine to coarse sand and fine to medium gravel			
45	57	fine to coarse sand and medium to coarse gravel with few cemented streaks			
57	58	gray shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 07/08/1996 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 07/09/96
Under the business name of Harp Well & Pump Service, Inc. by (signature)

Todd S. Harp