

1 LOCATION OF WATER WELL: Sumner		FRACTION 1/4 C of SW 1/4		Section Number 21	Township Number T 31 S	Range Number R 2E E/W
Distance and direction from nearest town or city street address of well if located within city? 2 m. E., 3 m. S., 1 m. E., 3/4 m. S., 1/4 m. E. of Belle Plaine, Kansas						
WATER WELL OWNER: HOOBLE, Curt		Board of Agriculture, Division of Water Resource				
RR#, ST. ADDRESS, BOX #: 1345 E. 130th North		Application Number: 41,946				
CITY, STATE, ZIP CODE: Mulvane, Kansas 67110						
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL 48 ft. ELEVATION: Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 12 FT. BELOW LAND SURFACE MEASURED ON 07/09/1996 Pump test data: Well water was 1 ft. after 2 hours pumping 3 gpm Est. Yield 600 gpm: Well water was 1 ft. after 2 hours pumping 3 gpm Bore Hole Diameter 30 in. to 48 ft. and 1 in. to 2 ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well 2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 7 Lawn and garden only 10 Monitoring well				
Was a chemical/bacteriological sample submitted to Department? Yes ☐ No ☒ ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes ☒ No ☐						
5 TYPE OF CASING USED:		CASING JOINTS:				
1 Steel 3 RMP (SR)		5 Wrought iron 8 Concrete tile Glued X Clamped				
2 PVC 4 ABS		6 Asbestos-Cement 9 Other (Specify below) Welded				
		7 Fiberglass SDR-26 Threaded				
Blank casing Diameter 16 in. to 20 ft., Dia in. to ft., Dia in. to ft.						
Casing height above land surface 12 in., weight 19.750 lbs. / ft. Wall thickness or gauge No. .616						
TYPE OF SCREEN OR PERFORATION MATERIAL:						
1 Steel 3 Stainless Steel 5 Fiberglass 7 PVC 10 Asbestos-cement						
2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 other (specify)						
12 None used (open hole)						
SCREEN OR PERFORATION OPENING ARE:						
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)						
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes						
7 Torch cut 10 Other (specify)						
SCREEN-PERFORATION INTERVALS: from 20 ft. to 48 ft., From ft. to ft.						
GRAVEL PACK INTERVALS: from 20 ft. to 48 ft., From ft. to ft.						
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug						
Grout Intervals: From 0 ft. to 20 ft. From ft. to ft. From ft. to ft.						
What is the nearest source of possible contamination:						
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandon water well						
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well						
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)						
13 Insecticide storage None Apparent						
Direction from well? How many feet?						
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS	
0	4	soil				
4	10	tan clay				
10	17	fine sand				
17	25	medium to coarse sand with clay streaks				
25	48	medium to coarse sand and gravel (loose)				
48	49	blue shale				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 07/09/1996 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 07/10/96 Under the business name of Harp Well & Pump Service, Inc by (signature) Todd S. Harp						