WATE	R WEL	L RECORD	Form W	WC-5	Division of Wate	r Resources App. N	o.	
1 LOCATION OF WATER WELL: County: Summner		Fraction 1/4 1/4 SE	1/4 1/4	Section Number	Township No. T 31 S	Range Number R 2		
		ddress of Well Location; i			Global Positioning System (GPS) information:			
from	nearest to	own or intersection: If at o	owner's address, check	Latitude: (in decimal degrees)				
169	1692 E 30th Ave.				Longitude: (in decimal degrees)			
Oxf	Oxford, KS 67119				Elevation:			
2 WATER WELL OWNER: Chuck Buss					Datum: ☐ WGS 84, ☐ NAD 83, ☐ NAD 27 Collection Method:			
RR#, Street Address, Box #: 1692 E 30th Ave					GPS unit (Make/Model:)			
City State 7ID Code			KS 67119		☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey			
			10 07119		Est. Accuracy: -	3 m, 🔲 3-5 m, 🗀	5-15 m,	
3 LOCATE WELL								
I		I AN "X" IN 4 DEPTH OF COMPLETED WELL 50						
SEC	CTION BOX: Depth(s) Groundwater Encountered (1).10							
	Pump test data: Well water wasft. after hours pumping							
	ECT VIELD 1000 Well water and A - A - house numerical							
w N	W NI		er 30in. to .50ft., andin. toft.					
"								
	WELL WATER TO BE USED AS: Public water supply Geothermal Injection well Domestic Feedlot Oil field water supply Dewatering Other (Specify below)							
	☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☐ Monitoring well							
	Was a chemical/bacteriological sample submitted to Department? ☐ Yes ☑ No							
S If yes, mo/day/yr sample was submitted								
mile Water well disinfected? ✓ Yes □ No								
5 TYPE OF CASING USED: Steel PVC Other								
CASING JOINTS: 🗹 Glued 🔲 Clamped 🗎 Welded 🗎 Threaded								
Casing diameter .1.6 in. to .30 ft., Diameter in. to ft., Diameter ft.								
Casing height above land surface 12 in., Weight 15 lbs./ft., Wall thickness or gauge No. Sch40								
TYPE OF SCREEN OR PERFORATION MATERIAL:								
☐ Steel ☐ Stainless Steel ☐ PVC ☐ Other (Specify)								
SCREEN OR PERFORATION OPENINGS ARE:								
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)								
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)								
SCREEN-PERFORATED INTERVALS: From								
From ft. to ft., From ft. to ft.								
GRAVEL PACK INTERVALS: From								
Fromft. toft., Fromft. to								
6 GROUT MATERIAL: Neat cement Cement grout Denoting Other Grout Intervals: From 3 ft to 20 ft From ft to ft From ft to ft.								
Grout Intervals: From .3								
☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☑ Other (specify below)								
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well								
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well								
		well					LOCANO INTERVALO	
FROM	-	LITHOLOG	IC LUG	FROM	TO LITHO. LO	JG (cont.) or PLC	UGGING INTERVALS	
3	6	Top Soil						
6	20	Clay Fine Sand						
20	50	Med Sand						
20	100	ivieu Sariu		 				
	+ +			<u> </u>				
	 							
-								
	† † †							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ✓ constructed, ☐ reconstructed, or ☐ plugged								
under my jurisdiction and was completed on (mo/day/year) .4/8/10 and this record is true to the best of my knowledge and belief.								
Kansas Water Well Contractor's License No238 This Water Well Record was completed On (mo/day/year) .4/12/10								
under the business name of Premier Pump and Well Service, Inc. by (signature) Fature A News								
INSTRUCTIONS : Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send three copies								
(white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at								
http://www.kdheks.gov/waterwell/index.html.								
KSA 82a-1212 Check: White Copy, Delink Copy								