			WAT	ER WELL RECORD	Form WWC-5	KSA 82a-1	212 ID No. <u>00</u> 4				
1 LOCATI	ON OF WATE		Fraction			ction Number	Township Nu	ımber	Rang	e Numbe	r
	Co		NE ¼		NE ¼	5	⊤ 31	S	R	3	E
			wn or city street ac	ddress of well if locat ast St., Udall	ed within city?						
2 WATER	WELL OWNE	R: Kistle	r Service, Ind	<b>3</b> .							
RR#, St. Ad	ddress, Box#	: 301 E	. Hwy K-15				Board of Agric	ulture, Divis	sion of Wat	ter Resou	urces
City, State,	ZIP Code	: Udall,	KS 67146				Application Nu	mber:			
LOCATE	E WELL'S LO	CATON WITH	1 4		2.			1270	99 /TO	CI	
AN "X" II	N SECTION E	SOX:	DEPTHOF	COMPLETED WELL	3	tt. ELEV	ATION:	1219	00 (10	٠,	
I		×		dwater Encountered						1107109	- π.
	NW	NE	1	WATER LEVEL .						1/0//08	
Mile M				p test data: Well w							
₩ <b>-</b>			Est. Yield	gpm: Well w	ater was	<u>-</u> ft	. after	hours p	umping		gpm
1 1			Bore Hole Diam	eter <b>8.5</b> in. TO BE USED AS: c 3 Feed lot	to 3	5	ft. and	in.	to		ft.
	sw	SE	1 Domestic	C 3 Feed lot	6 Public waters 6 Oil field water	supply	9 Dewatering	11ng 11 12	Other (S	well pecify be	low)
↓ L			2 Irrigation	4 Industrial	7 Laws and gar	den (demestis	10 Monitoring	ll	01.101 (0)	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	,
	S										
				/bacteriological samp							was
5 7/05 0			submitted				ter Well Disinfected			No X	
	F BLANK CAS			5 Wrought Iron			CASING JOIN			Jamped	
		_	(SR)	6 Asbestos-Cen						<u> </u>	
2 PV		4 ABS		7 Fiberglass					ed		
Blank casing	g diameter	2	in. to 18	ft., Dia	in.	to	ft., Dia		in. to		ft.
Casing heig	ght above land	surface F	lushmount	in., weight	0.703	lbs./ft.	Wall thickness or	gauge No.	S	CH. 40	
			N MATERIAL:		7	PVC	10 Asbe	stos-ceme	nt		
1 Ste	eel	3 Stain	ess steel	5 Fiberglass	8	RMP (SR)	11 Other	r (specify)			
2 Bra				6 Concrete tile	9	ABS	12 None	used (ope	n hole)		
SCREEN O	R PERFORA				auzed wrapped		8 Saw cut		11 None	(open ho	le)
	ntinuous slot		Mill slot		ire wrapped		9 Drilled holes				
2 Lou	uvered shutter	4	Key punched		orch cut		10 Other (speci	fy)			
SCREEN-PI	ERFORATED	INTERVALS		18 ft. to							
			From	ft. to		ft. F	rom	ft. to			ft.
GR/	AVEL PACK I	NTERVALS:	From	15 ft. to	35	ft. F	rom	ft. to			ft.
			From	ft. to		ft. F	rom	ft. to	)		ft.
6 GROUT	MATERIAL:	1 Neat	cement 2	Cement grout	3 Ber	ntonite	4 Other				
Grout Interv	als From	1	ft. to 15	ft. From			ft. From		ft. to		
			contamination:				ock pens	14 Aba	ndoned wa	ater well	-
1 Sep	ptic tank		4 Lateral lines	7 Pit p	rivy	11 Fuels			well/ Gas w		
2 Sev	wer lines		5 Cess pool	8 Sewa	age lagoon	12 Fertiliz	zer storage	16 Oth	er (specify	below)	
3 Wa	tertight sewer	lines	6 Seepage pit	9 Feed	lyard	13 Insect	icide storage				
Direction fro						How many					
FROM	TO	CODE		OGIC LOG	FROM	ТО	PLU	GGING IN	TERVALS		
0	0.5		psoil	40 mod b 4-	E						
0.5	35		ay, dark brown me silt	to red brown to o	live,						
0.0	- 33	50	me ant								
							444				
					-						
_				ON: This water well	was (1) constru	cted, (2) recor	nstructed, or (3) plu	gged under	my jurisdi	ction and	was
	on (mo/day/yr)						ue to the best of m	-			
	Contractor's L			531		Vater Well Re	cord Nas complete	ed on (mo/d	lay/yr)	01/29/	80
under the bu	usiness name	of	Geotechnic	al Services In	c. by	(signature)	de K				
INSTRU	UCTIONS: Ple	ase fill in blank	s and circle the corr	ect answers. Send the	ee copies to Kans	sas Department	of Health and Envir	onment, Bur	eau of Wate	er, 1000 S	W
Jacksor	n St., Ste. 420,	ropeka, Kansa	as 66612-1367. Tele	ephone: 913-296-5545	o. Send one to W	A I ER WELL O	vvivien and retain/or	ne for your re	cords.		