				R WELL RECORD					
	ON OF WATE		1		I	ection Number	· ·		
County:			SE ½				т 31	S R 3	E
	d direction from Utility Pole		own or city street add	dress of well if loc	ated within city				
2 WATER	WELL OWNE	R: Kistle	er Service, Inc.						
RR#, St. Ad	dress, Box #	: 301 E	E. Hwy K-15				Board of Agricul	ture, Division of Water Resour	rces
City State	7IP Code	· Udall	. KS 67146				Application Num	nber:	
LOCATE	WELL'S LOC N SECTION B	ATON WIT	HI.	OMPLETED WEI	1	24 ft FLF	VATION:	1273.97 (TOC)	
┰″``^ ''	i I		Denth(s) Ground	water Encountere	 d 1	16	ft 2	ft. 3	A .
			WELL'S STATIC	MARCE ERCOURTER	14.2	ft below TOO	measured on moldar	y/yr 07/17/08	. "
	NW	- NE	Pump	test data: Well	water was	it. Delow 100	ft after	hours pumping g	
∯ w L									
₹ " Г			Pero Hole Diame	gpill. well	water was	25	ft and	hours pumping g	Pill
L_	sw	. SF	WELL WATER T	O BE USED AS:	5 Public water	er supply	8 Air conditioni	na 11 Injection well	. ".
	ï		1 Domestic	3 Feed lot	6 Oil field wa	ter supply	9 Dewatering	in. to ng 11 Injection well 12 Other (Specify belo	ow)
† L		i X	2 Irrigation	4 Industrial	7 Lawn and	garden (domes	tic) 10 Monitoring	well	
	S							If yes, mo/day/yr sample w	98
			submitted		•		ater Well Disinfected		1
5 TYPE O	F BLANK CAS	ING USED		5 Wrought Iro	n 8 Cc	ncrete tile	CASING JOINT	S: Glued Clamped	
1 Ste		3 RMI		6 Asbestos-C				Welded	
2 PV		4 ABS	` '	7 Fiberglass			· .	Threaded Flush	
				-		in to		in. to	
Ossina bala	g diameter		Fluehmount	in weight	0.703	lhe #	Wall thickness or a	auge No. SCH. 40	- "
Type of c	INT above land	SUTTACE	ION MATERIAL:	in., weight		7 D\/C	10 Asbes	auge No. COII. 40	
1 Ste		2 Stai	nless steel	5 Eiberglass		9 PMP (SP)	11 Other	(cpecify)	
2 Bra		3 Stat	nless steel vanized steel	6 Concrete tile	e	9 ABS	12 None	(specify) used (open hole)	
		TION OPEN	INGS ARE:	5	Gauzed wrapp	ed	8 Saw cut	11 None (open hole	e)
	ntinuous slot		3 Mill slot	6	Wire wrapped		9 Drilled holes	• •	
2 Lou	uvered shutter		4 Key punched		Torch cut		10 Other (specify	y)	
	ERFORATED				24	ft.	From	ft. to	ft.
								ft. to	
GR	AVEL PACK	NTERVALS						ft. to	
	,		From				From		ft.
6 GROUT	MATERIAL:	1 Nea	at cement 2	Cement grout	3	Bentonite	4 Other		
Grout Interv	als From	1	ft. to 8	ft. From	•	ft. to	ft. From	ft. to	ft.
			le contamination:					14 Abandoned water well	
1		•		7 Pi	t privy		•	15 Oil well/ Gas well	
			5 Cess pool		ewage lagoon		12 Fertilizer storage 16 Other (specify below)		
1	atertight sewer	lines	6 Seepage pit		eedyard		ecticide storage		
Direction fro	om well?					How mar	ny feet?		
FROM	TO	CODE		OGIC LOG	FRO	M TO	PLU	GGING INTERVALS	
0	0.5		Topsoil, dark bro						
			Clay, brown to re crystalline calcium		n				
0.5	8		rystalline calcium imestone layer	i vai sviiate, tilli	'				
8	9		_imestone	,					
9	25		Clay, olive to red	brown					
	ļ								
	ļ	ļ							
	-	-				-			
<u> </u>									
7 CONTR	ACTOR'S OP	I ANDOW!	VER'S CERTIFICAT	ION: This water w	vell was (1) con	structed (2) re	constructed or (3) plus	gged under my jurisdiction and	wee
_				4/08					
	on (mo/day/yr)			531	. .		, n	y knowledge and belief. Kansi ed on (mo/day/yr) 08/11/0	
1			Geotechnie		•		Record vas complete		
unger the b	usiness name	OT	Georechill	ai Seivices	Hito.	by (signature	ant of Halth and day	onment, Bureau of Water, 1000 S	14/
INSTR	RICTIONS DI	ease fill in hi	anks and circle the cor	rect answers Send	Three conies to				