

1 LOCATION OF WATER WELL
 County: Cowley Fraction nw 1/4 nw 1/4 nw 1/4 Section Number 12 Township Number T 31 S Range Number R 5 E/W

Distance and direction from nearest town or city? Wilmont 2 Mi East Street address of well if located within city?

2 WATER WELL OWNER: James Craig
 RR#, St. Address, Box # :
 City, State, ZIP Code : Ponca City Oklahoma 74601
 Board of Agriculture, Division of Water Resources
 Application Number:

3 DEPTH OF COMPLETED WELL: 85 ft. Bore Hole Diameter: 1.0 in. to T.D. ft., and in. to ft.
 Well Water to be used as:
1 Domestic 3 Feedlot 5 Public water supply 6 Oil field water supply 7 Lawn and garden only 8 Air conditioning 9 Dewatering 10 Observation well 11 Injection well 12 Other (Specify below)
 2 Irrigation 4 Industrial
 Well's static water level: 4.5 ft. below land surface measured on Sept month 20 day 1979 year
 Pump Test Data Bail test: Well water was ft. after hours pumping gpm
 Est. Yield 1 1/2 gpm: Well water was ft. after hours pumping gpm

4 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 6 Asbestos-Cement 7 Fiberglass 8 Concrete tile 9 Other (specify below) Casing Joints: Glued X Clamped Welded Threaded
 2 PVC X 4 ABS
 Blank casing dia 5 in. to 7.5 ft., Dia in. to ft., Dia in. to ft.
 Casing height above land surface: 16 in., weight 2.8 lbs./ft. Wall thickness or gauge No. sch 40
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 11 Other (specify)
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
 Screen or Perforation Openings Are:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut X 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify)
 Screen-Perforation Dia 5 in. to ft., Dia in. to ft., Dia in. to ft.
 Screen-Perforated Intervals: From 7.5 ft. to 85 ft., From ft. to ft., From ft. to ft.
 Gravel Pack Intervals: From 15 ft. to 85 ft., From ft. to ft., From ft. to ft.

5 GROUT MATERIAL: 1 Neat cement X 2 Cement grout 3 Bentonite 4 Other
 Grouted Intervals: From 0 ft. to 15 ft., From ft. to ft., From ft. to ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Cess pool 7 Sewage lagoon X 11 Fertilizer storage 14 Abandoned water well
 2 Sewer lines 5 Seepage pit 8 Feed yard 12 Insecticide storage 15 Oil well/Gas well
 3 Lateral lines 6 Pit privy 9 Livestock pens 13 Watertight sewer lines 16 Other (specify below)
 Direction from well se How many feet 300 ? Water Well Disinfected? Yes X No
 Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, date sample was submitted month day year Pump Installed? Yes X No
 If Yes: Pump Manufacturer's name Pumpco Supply Model No. 102S58 HP 1/2 Volts 230
 Depth of Pump Intake 80 ft. Pumps Capacity rated at 10 gal./min.
 Type of pump: X 1 Submersible 2 Turbine 3 Jet 4 Centrifugal 5 Reciprocating 6 Other

6 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on Sept month 20 day 1979 year
 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 171.
 This Water Well Record was completed on Oct month 6 day 1979 year under the business name of G & S Drilling by (signature)

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
	0	5	Bkn wht lm			
	5	45	wht lm med/ hard			
	45	65	blu sh med			
	65	75	red bed			
	75	85	blu sh & lm shells			
ELEVATION:						

Depth(s) Groundwater Encountered 1. 40/45 ft. 2. ft. 3. ft. 4. ft. (Use a second sheet if needed)

INSTRUCTIONS: Use typewriter or ball point pen, please press firmly and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Water Well Contractors, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY
T
31
R
5
EW
SEC
12
NW 1/4
NW 1/4
NW 1/4