| WATER WELL RECORD | Form WV | VC-5 Di | | Resources App. No | | |
|--|-----------------------------|---|--|--------------------------|-------------------------|--|
| 1 LOCATION OF WATER WE County: Montgomery | LL: Fraction 1/4 NE 1/4 NE | • | on Number 25 | Township No. T 32 S | Range Number R 15 ☑E □W | |
| Street/Rural Address of Well Lo from nearest town or intersection Earth Care Products (Former 800 North 21st Street, | here . Latitude Long Eleva | Global Positioning System (GPS) information: Latitude: .N37.231752777 | | | | |
| 2 WATER WELL OWNER: Earth Care Products (Former ACC) RR#, Street Address, Box #: 800 North 21st Street City, State, ZIP Code : Independence, Kansas 67301 | | r ACC) Collect | Datum: ☐ WGS 84, ☐ NAD 83, ☐ NAD 27 Collection Method: ☐ GPS unit (Make/Model:) ☐ Digital Map/Photo, Topographic Map, ☐ Land Survey Est. Accuracy: | | | |
| 3 LOCATE WELL WITH AN "X" IN SECTION BOX: N Depth(s) Groundwater Encountered (1) Dry. ft. (2) N/A. ft. (3) N/A ft. WELL'S STATIC WATER LEVEL Dry. ft. below land surface measured on mo/day/yr. 3.20 (5.5) Pump test data: Well water was. N/A. ft. after. N/A. hours pumping. N/A. gpm EST. YIELD. N/Agpm. Well water was. N/A. ft. after. N/A. hours pumping. N/A gpm Bore Hole Diameter 8.25. in. to 1.0.5 ft., and 1.0 in. to 1.0 ft. WELL WATER TO BE USED AS: Public water supply Geothermal Injection well Domestic Feedlot Oil field water supply Dewatering Other (Specify below) Irrigation Industrial Domestic-lawn & garden Monitoring well Was a chemical/bacteriological sample submitted to Department? If yes, mo/day/yr sample was submitted N/A. Water well disinfected? Yes No | | | | | | |
| 5 TYPE OF CASING USED: Steel PVC Other CASING JOINTS: Glued Clamped Welded Threaded Casing diameter 2. in. to 4. ft., Diameter N/A in. to N/A ft., Diameter N/A in. to N/A ft. Casing height above land surface in., Weight N/A lbs./ft., Wall thickness or gauge No. Schedule 40. TYPE OF SCREEN OR PERFORATION MATERIAL: Steel Stainless Steel PVC Other (Specify) Brass Galvanized Steel None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole) Louvered shutter Key punched Wire wrapped Saw cut Other (specify) SCREEN-PERFORATED INTERVALS: From N/A ft. to N/A ft. From N/A ft. to N/A ft. ft. GRAVEL PACK INTERVALS: From N/A ft. to N/A ft. to N/A ft. Threaded Threaded Interval in to N/A ft. to N/A ft. Threaded Threaded Interval in to N/A ft. Threaded Interval Int | | | | | | |
| GROUT MATERIAL: Neat cement Cement grout Bentonite Other Concrete 0 to 2 | | | | | | |
| 0 4 Fill 4 5 CAY-GR | HOLOGIC LOG | FROM TO | LITHO. L | OG (cont.) <u>or</u> PLI | UGGING INTERVALS | |
| 5 10 c) by - 0 10 10.5 Limeston | ive yellow | | | | | |
| | | | | | | |
| 7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo/day/year) | | | | | | |