WATE	R WELL RE	CORD	Form W	WC-5	Division of Water Resources App. No.
	CATION OF W		Fraction		Section Number Township No. Range Number
			SW 1/4 NE 1/4 SE		4 32 T 32 S R 16 ZE W
					Global Positioning System (GPS) information:
i	from nearest town or intersection: If at owner's address, check here				Latitude: (in decimal degrees) Longitude: (in decimal degrees)
One mile east of Independence, KS				Elevation: (in decimal degrees)	
					Datum: WGS 84, NAD 83, NAD 27
	TER WELL O	i ioui iiu	nd Cement Compan	ıv	Collection Method:
RR#, Street Address, Box #: 1765 Limestone Rd.			mestone Rd.		GPS unit (Make/Model:)
City	, State, ZIP Code	^{e :} Indeper	idence, KS 67301		☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey Est. Accuracy: ☐ <3 m, ☐ 3-5 m, ☐ 5-15 m, ☐ >15 m
3 LOCATE WELL					
	H AN "X" IN	4 DEPTH OF	COMPLETED WEL	L 22	ft.
SEC	TION BOX:	Depth(s) Ground	lwater Encountered	(1)	ft. (2) ft. (3) ft.
					it. below land surface measured on mo/day/yr. 2/27/09
					ft. after hours pumping gpm
N	W NE				ft. after hours pumping gpm
W Bore Hole Diameter 8.1/2in. to .22ft., andin. to					
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well Domestic Feedlot Oil field water supply Dewatering Other (Specify below					
SW - SE - Domestic Feedlot Oil field water supply Dewatering Other (Specify below) Irrigation Industrial Domestic-lawn & garden ✓ Monitoring well					
Was a chemical/bacteriological sample submitted to Department? Yes No					
S If yes, mo/day/yr sample was submitted					
1 mile Water well disinfected? ☐ Yes ☑ No					
5 TYPE OF CASING USED: Steel PVC Other					
CASING JOINTS: Glued Clamped Welded Threaded					
Casing diameter .2 in. to .10 ft., Diameter ft., Diameter ft.					
Casing height above land surface. 3 ft in., Weight SCH 40lbs./ft., Wall thickness or gauge No					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
Steel Stainless Steel PVC Other (Specify)					
Brass Galvanized Steel None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE: Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)					
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)					
SCREEN-PERFORATED INTERVALS: From. 22. ft. to7. ft., From ft. to ft.					
			From	ft. to	ft., From ft. to ft.
GRAVEL PACK INTERVALS: From					
From					
6 GROUT MATERIAL: Neat cement Cement grout Dentonite Other					
	ntervals: From	n .x It. to	!	n	. π. to π., From π. toπ.
What is the nearest source of possible contamination: ☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☑ Other (specify below)					
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well					
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well					
	ction from well.				e from wellN/A
FROM	TO	LITHOLOG		FROM	TO LITHO. LOG (cont.) or PLUGGING INTERVALS
0'		l: Coarse, road p			
3'		lay: r to y brn; firr		-	
	8' Wet	ately plastic; moi	St	 	
8'		ued Silty Clay to	TD of 22'		
0	ZZ Conti	ided Silly Clay to	10 01 22	 	
	OLGW	/-8			
	0_0				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☑ constructed, ☐ reconstructed, or ☐ plugged					
under my jurisdiction and was completed on (mo/day/year) .2/24/09 and this record is true to the best of my knowledge and belief.					
Kansas Water Well Contractor's License No665 This Water Well Record was completed on (mo/day/year) .4/7/09					
under the business name of Pratt Well Service. Inc. by (signature)					
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send three copies (white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.					
Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at					
http://www.kdheks.gov/waterwell/index.html.					
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy					