

1 LOCATION OF WATER WELL: Fraction SW 1/4 NW 1/4 SE 1/4 Section Number 31 Township Number T 32 S Range Number R 17 EW

Distance and direction from nearest town or city street address of well if located within city? 1/4 miles N of Coffeyville on US 169/96 junction

2 WATER WELL OWNER: Resource Recovery, Inc. MW-5 Board of Agriculture, Division of Water Resources RR#, St. Address, Box #: P.O. Box 306 Application Number: City, State, ZIP Code: Cherryvale, KS 67339

3 LOCATE WELL'S LOCATION WITH AN 'X' IN SECTION BOX: [Diagram] 4 DEPTH OF COMPLETED WELL: 17.5 ft. ELEVATION: 844 ft MSL. WELL'S STATIC WATER LEVEL: Dry ft. below land surface measured on mo/day/yr 5/28/98. TYPE OF BLANK CASING USED: 2 PVC. TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC. SCREEN-PERFORATED INTERVALS: 7.0 ft. to 17.0 ft. GRAVEL PACK INTERVALS: 4.0 ft. to 17.0 ft.

5 TYPE OF BLANK CASING USED: 1 Steel, 2 PVC, 3 RMP (SR), 4 ABS, 5 Wrought iron, 6 Asbestos-Cement, 7 Fiberglass, 8 Concrete tile, 9 Other (specify below), 10 Asbestos-cement. CASING JOINTS: Glued, Clamped, Welded, Threaded. Blank casing diameter: 2 in. Dia: 7.0 ft. Casing height above land surface: 30 in., weight: lbs./ft. Wall thickness or gauge No. 40. TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel, 2 Brass, 3 Mill slot, 4 Key punched, 5 Fiberglass, 6 Concrete tile, 7 PVC, 8 RMP (SR), 9 ABS, 10 Other (specify). SCREEN-PERFORATED INTERVALS: From 7.0 ft. to 17.0 ft. GRAVEL PACK INTERVALS: From 4.0 ft. to 17.0 ft.

6 GROUT MATERIAL: 1 Neat cement, 2 Cement grout, 3 Bentonite, 4 Other. Grout Intervals: From 1.0 ft. to 4.0 ft. What is the nearest source of possible contamination: 1 Septic tank, 2 Sewer lines, 3 Watertight sewer lines, 4 Lateral lines, 5 Cess pool, 6 Seepage pit, 7 Pit privy, 8 Sewage lagoon, 9 Feedyard, 10 Livestock pens, 11 Fuel storage, 12 Fertilizer storage, 13 Insecticide storage, 14 Abandoned water well, 15 Oil well/Gas well, 16 Other (specify below) SLF. Direction from well? NE. How many feet? 400.

LITHOLOGIC LOG and PLUGGING INTERVALS table with columns FROM, TO, LITHOLOGIC LOG, FROM, TO, PLUGGING INTERVALS. Entries include Silty Clay (0-3'), Weathered Clayshale (3'-14.2'), and Gray Shale (Cherryvale) (14.2'-17.5').

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5/27/98 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 568 This Water Well Record was completed on (mo/day/yr) 6/8/98 under the business name of MAXS by (signature) David Hungler